

Maximum Portable Cooling for Your Large Professional Environment

The Climate Pro K63e brings “roll-it-in, set-it-up and plug-it-in” convenience with the innovative features that distinguish the entire Climate Pro line.

Key Features

- Operates on 3 Phase, 460V electricity.
- Cools to mid-60s°F — for effective heat control around electronics, servers, and computers.
- Provides 60,000 Btu/h of cool air — maximum spot cooling to just the room that needs it.
- Digital controls and auto operation — allow 24/7 programmable back-up of central systems.
- Effective moisture removal — hastens drying for humid and water-damaged areas.
- Connectivity ready with remote monitoring, geolocation and performance notifications.*

*Subscription required. See your local dealer for details.



Ideal for . . .

Offices
Server and Telecom Rooms
Hospitals
Schools
Laboratories
Banks
Emergency Back-up
Supplemental Cooling
After-hours Cooling
Retail Spaces

Another line of quality products by DENSO.

DENSO

MovinCool is a brand of DENSO Corporation, the world's largest manufacturer of spot air conditioners. MovinCool spot air conditioners and heat pumps are backed by a full three-year on-site parts and labor warranty with registration— the strongest in the industry.



Climate Pro® K63e Specifications

		K63e
Electronic Features	Control Panel	Programmable
Cooling Capacity	Rating Conditions: 95°F @ 60% RH	60,000 Btu/h
Energy Efficiency Rating (EER)		9.1
Electrical Characteristics	Voltage Requirement (60 Hz)	3 Phase, 460 V
	Total Power Consumption	6.6 kW
	Current Consumption	9.5 amps
	Recommended Fuse Size	20 amps
	NEMA Plug Configuration	L16 - 20P
	Min. - Max. Voltage	440 - 480 V
Fan Motor Output	Evaporator	0.56 kW
	Condenser(s)	0.30 kW x 2 motors
Evaporator	Fan Type	Centrifugal
	Max. Air Flow - High/Mid/Low	1770 / 1710 / 1651 CFM*
	Max. External Static Pressure	0.9 IWG
Condenser	Fan Type	Centrifugal
	Max. Air Flow - High/Low	2400 CFM*
	Max. External Static Pressure	0.85 IWG
Compressor	Type	Hermetic Scroll
	Output	3.45 kW
Refrigerant	Type	R-32
	Amount	3.22 lb
Dimensions	W x D x H	31 x 55 x 64 in
Net Weight/Shipping Weight		635 / 729 lb
Power Cord	Gauge	12 AWG (4-core)
	Length	6 ft
Condensate Tank Capacity (approx.)		Auto Pump Included
Operating Conditions	Min. - Max. @ 50% RH	65° - 105°F
Max. Duct Length	Per Cold Duct Hose	40 ft
	Hot Duct Hose	100 ft
Max. Sound Level (high/mid/low)	With Condenser Duct	71 / 70 / 69 dB(A)
	Without Condenser Duct	71 / 70 / 69 dB(A)

*All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit [MovinCool.com/](https://www.MovinCool.com/) warranty for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

DENSO Products and Services Americas, Inc.
 3900 Via Oro Avenue | Long Beach CA 90810 USA
 +1-800-264-9573 | [MovinCool.com](https://www.MovinCool.com)

