

The Cooler Choice for Your Warehouse or Factory

The Climate Pro X20e brings advanced spot-cooling to commercial and industrial applications — perfect for cooling people and production processes.

Key Features

- Air-cooled units at 16,800 Btu/h to handle temperatures as high as 113°F.
- Three-speed fan and adjustable nozzles for versatile cooling comfort.
- Digital controls and auto operation — for 24/7 programmable back-up of central systems.
- Effective moisture removal — hastens drying for humid and water-damaged areas.
- Connectivity ready with remote monitoring, geolocation and performance notifications.*

*Subscription required. See your local dealer for details.



Ideal for . . .

Warehouses
Assembly Lines
Manufacturing Plants
Process Cooling
Construction Sites
Moisture Removal
Special Events

Another line of quality products by DENSO.

DENSO

MovinCool is a brand of DENSO Corporation, the world's largest manufacturer of spot air conditioners. MovinCool spot air conditioners and heat pumps are backed by a full three-year on-site parts and labor warranty with registration— the strongest in the industry.



Climate Pro® X20e Specifications

X20e		
Electronic Features	Control Panel	Programmable
Cooling Capacity	Rating Conditions: 95°F @ 60% RH	16,800 Btu/h
Energy Efficiency Ratio (EER)		10.5
Electrical Characteristics	Voltage Requirement (60 Hz)	1 Phase, 115 V
	Total Power Consumption	1.6 kW
	Current Consumption	14.5 amps
	Recommended Fuse Size	20 amps
	NEMA Plug Configuration	5-20P
	Min. Max. Voltage	104 – 127 V
Fans	Motor Output	0.37 kW
Evaporator	Fan Type	Centrifugal
	Max Air Flow (high/mid/low)	565 / 525 / 475 CFM
	Max External Static Pressure	0.31 IWG
Condenser	Fan Type	Centrifugal
	Max Air Flow (high/mid/low)	1000 / 930 / 830 CFM
	Max External Static Pressure	0.23 IWG
Compressor	Type	Hermetic Rotary
	Output	0.75 kW
Refrigerant	Type	R-32
	Amount	1.12 lb
Dimensions	W x D x H	22 x 29 x 51 in
Net Weight/Shipping Weight		192 / 234 lb
Power Cord	Gauge	12 AWG (3-core)
	Length	10 ft
Condensate Tank Capacity (approx.)		5 gal
Operating Conditions	Min. – Max. @ 50% RH	70° – 113°F
Max. Duct Length	Per Cold Duct Hose	30 ft
	Hot Duct Hose	60 ft
Max. Sound Level (high/mid/low)	With Condenser Duct	67 / 66 / 65 dB(A)
	Without Condenser Duct	67 / 66 / 65 dB(A)

*All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit [MovinCool.com/warranty](https://www.MovinCool.com/warranty) for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

DENSO Products and Services Americas, Inc.
 3900 Via Oro Avenue | Long Beach CA 90810 USA
 +1-800-264-9573 | [MovinCool.com](https://www.MovinCool.com)

