



The Cooler Choice for Your Large Office or Computer Room

The all-new Climate Pro K60 brings “roll-it-in, set-it-up and plug-it-in” convenience with the innovative features that distinguish the entire Climate Pro line.

Key Features

- Operates on 1 Phase, 208/230V electric.
- Cools to mid-60s°F — for effective heat control around electronics, servers, and computers.
- Provides 60,000 Btu/h of cool air — maximum spot cooling to just the room that needs it.
- Digital controls and auto operation — allow 24/7 programmable back-up of central systems.
- Effective moisture removal — hastens drying for humid and water-damaged areas.



Ideal for . . .

- Offices
- Server and Telecom Rooms
- Hospitals
- Schools
- Laboratories
- Banks
- Emergency Back-up
- Supplemental Cooling
- After-hours Cooling
- Retail Spaces

Another line of quality products by DENSO.

DENSO

MovinCool is a brand of DENSO Corporation, the world's largest manufacturer of spot air conditioners. MovinCool spot air conditioners and heat pumps are backed by a full three-year on-site parts and labor warranty with registration — the strongest in the industry.



Climate Pro K60 Specifications

		K60
Electronic Features	Control Panel	Programmable
Cooling Capacity	Rating Conditions: 95°F @ 60% RH	60,000 Btu/h
Electrical Characteristics	Voltage Requirement (60 Hz)	1 Phase, 208/230 V
	Total Power Consumption	6.6 kW*
	Current Consumption	31.5 amps*
	Recommended Fuse Size	50 amps
	NEMA Plug Configuration	6-50P
	Min. - Max. Voltage	198 - 253 V
Fans	Motor Output	0.56 kW Evaporator 0.30 kW x 2 Condensers
Evaporator	Fan Type	Centrifugal
	Max. Air Flow - High/Mid/Low	1770/1710/1650 CFM
	Max. External Static Pressure	0.9 IWG
Condenser	Fan Type	Centrifugal
	Max. Air Flow - High/Mid/Low	2400 CFM
	Max. External Static Pressure	0.85 IWG
Compressor	Type	Hermetic Rotary
	Output	3.45 kW
Refrigerant	Type	R-410A
Dimensions	W x D x H	31 x 55 x 64 in
Net Weight/Shipping Weight		582/683 lb
Power Cord	Gauge	6 AWG (3-core)
	Length	6 ft
Condensate Tank Capacity		Auto Pump Included
Operating Conditions	Min. - Max. @ 50% RH	65° - 105°F
Max. Duct Length	Per Cold Duct Hose	40 ft
	Hot Duct Hose	100 ft
Max. Sound Level	With Condenser Duct - High/Mid/Low	69/68/67 dB(A)
	Without Condenser Duct - High/Mid/Low	71/70/69 dB(A)

*Specifications information shown with 230 V. All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit MovinCool.com/warranty for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

DENSO Products and Services Americas, Inc.
3900 Via Oro Avenue | Long Beach CA 90810 USA
800-264-9573 | MovinCool.com

