

PI363418

FEATURES

Blower required (internal, in-line or remote blowers available)

Bright halogen lighting

Handfinished with hemmed edges and welded seams

Heat sentry for safety

Infinite speed blower control

Recessed controls for sleeker look

Heavy-duty stainless steel construction

Transition with backdraft minimizes backward flow of cold air

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

6", 12", 18" and 24" high stainless steel duct covers

Make-up air damper

Accessories available through an authorized Sub-Zero dealer.
For local dealer information, visit subzero-wolf.com/locator.



BLOWER OPTIONS


- 350 CFM Internal
- 450 CFM Internal
- 1200 CFM Internal
- 1100 CFM Inline
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote
- 600 CFM Internal
- 900 CFM Internal



PRODUCT SPECIFICATIONS

Model	PI363418
Dimensions	36"W x 18"H x 34"D
Weight	95 lb
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



DIMENSIONS

