

**PW362418**

## FEATURES

Heavy-duty stainless steel construction

Handfinished with hemmed edges and welded seams

Bright halogen lighting

Infinite speed blower control

Heat sentry for safety

Recessed controls for sleeker look

Blower required (internal, in-line or remote blowers available)

Transition with backdraft minimizes backward flow of cold air

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

## ACCESSORIES

600 CFM In-Line Blower

38" high stainless steel backsplash with or without warming racks

6", 12", 18", 24" and 30" high stainless steel duct covers

Horizontal discharge kit

Make-up air damper

Recirculating kit and filter for non-ducted applications (internal blower)

Accessories available through an authorized Sub-Zero dealer.  
For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).



## BLOWER OPTIONS


- 300 CFM Internal
- 450 CFM Internal
- 1100 CFM Inline
- 1200 CFM Remote
- 1500 CFM Remote
- 600 CFM Internal
- 900 CFM Internal
- 900 CFM Remote



PRODUCT SPECIFICATIONS

Model	PW362418
Dimensions	36"W x 18"H x 24"D
Weight	78 lb
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical or Horizontal
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



DIMENSIONS

