







H 6880 BP Features:

- M Touch controls are both easy to operate and navigate. An intuitive swipe of the screen will quickly lead you to your desired selection
- · Self Clean Oven
- 19 Operating Modes including Moisture Plus (plumbed only) increases the humidity in the oven optimizing the cooking of a variety of foods
- MasterChef Plus fully functional automatic programs to create 15 different types of bread at home
- MasterChef menu offers over 100 food types to cook to perfection
- Wireless Roast Probe for safe. easy handling and perfect roasting results
- Favorites up to 20 recipes
- Sabbath Program
- · CleanGlass Door
- TwinPower Fans provide optimum and even distribution of hot air
- Soft Open and Soft Close for easier handling
- The simple yet sleek Silhouette handle seems to float enhancing its modern design lines








SPECIFICATIONS	
H 6880 BP — Item 22688053USA	
Overall Unit Width - Excluding Fascia Dimension	28 ⁷ / ₁₆ " (722mm)
	· · · · · · · · · · · · · · · · · · ·
Overall Height - Excluding Fascia Dimension Overall Unit Depth - Excluding Fascia Dimension	27³/₄" (705mm)
Over Door Clearance	23³/4" (603mm)
	23" (584mm)
Overall Oven Interior Capacity	4.63 cu.ft - 131.24 liters
Overall Fascia Dimensions	29 ¹⁸ / ₁₆ " (757mm) W x 28 ⁵ / ₈ " (727mm) H x ⁷ / ₈ " (23mm) D
Oven Interior Dimensions	24 ¹ / ₂ " (622mm) W x 16 ⁵ / ₈ "(423mm) H x 18 ¹ / ₄ " (464mm) D
Built-In	
Minimum Cabinet Width	281/2" (724mm)
Minimum Cabinet Depth	24" (610mm)
Minimum Cabinet Opening Height	281/4" (718mm)
Minimum Base Support	193 lbs
Additional Cut-outs Required	Venting cut-out required at base of cabinet (4" x 28" / 100mm x 720mm) in the bottom of the cabinet for power cord and ventilation
Plumbing	
Plumbing Requirements	An Inline water filter, like activated carbon, is required to reduce mineral deposits. Do not connect to a Reverse Osmosis (RO) water system. Connect to a cold water supply only not to exceed 140°F (60°C). Must be connected to a shut-off valve. The water shut-off valve must be accessible after installation. The water pressure must be between 14.5 and 145 psi (1 and 10 bars). If the pressure is higher, install a pressure-reducing valve. The supplied hose has a length of 4' 11" (1.5 m). The hose must not be shortened.
Electrical	
Electrical Requirements	208/240V 30A 60Hz circuit
Power Cord	Yes - NEMA 14-30 plug
Electrical Rating	120/208V, 30A, 60Hz 5800w / 120/240V, 30A, 60Hz 4400w
Total Amps	240V / 24.166A / 208V / 21.15A
Shipping	
Shipping Weight	216 lbs
Shipping Dimensions	$32^{11}/_{16}$ " W x $35^{1}/_{16}$ " H x $30^{5}/_{16}$ " L
Support	
Call	800.843.7231
20/20	⁴2020technologies.com




PRODUCT VIEWS

Isometric




Front






PRODUCT VIEWS

Top View




Rear View






PRODUCT VIEWS

Side View



INSTALLATION SPECIFICATIONS

Install in Tall Cabinet





INSTALLATION SPECIFICATIONS

Undercounter Installation

