



Color Variants

RB492701
with temperature controlled drawer
fully integrated

Optional accessories

RA450000
Mechanical particle filter
RA450010
Activated charcoal filter for water filter
system including saturation indicator

RB492701

**Two-door bottom freezer with
integrated ice maker**
**with temperature controlled drawer
fully integrated**
Width 36" (91.4 cm)

- Width 36" (91.4 cm)
- Stainless steel interior
- Generous LED lighting concept
- Solid aluminum door bins
- Net volume 19.7 cu.ft.
(557 liters)
- Integrated automatic ice maker with
fixed water connection in the freezer
drawer
- One motorized glass shelf,
adjustable when fully loaded
- One asymmetrically split glass shelf
- Fully extendable freezer drawer with
practical divider
- ENERGY STAR® qualified

Operation

Electronic precision temperature
control with digital temperature display.

Technical features

Dynamic cool air distribution with
Multi-Flow Air System.
Automatic defrosting with defrost water
evaporation.
Activated charcoal air filter.
Energy-saving vacation mode.
Open-door and malfunction warning
system.

Cooling compartment

Net volume 14.3 cu. ft.
No-frost technology with fast cooling.
Temperature adjustable from 35 °F to
46 °F (+2 °C to +8 °C).
2 safety glass shelves, 1 of which is
motorized.
1 asymmetrically split safety glass
shelf, manually adjustable.
2 fully extendable drawers with
transparent front.
Bright interior lighting with LED sidewall
pillars.
2 height adjustable door bins, one large
gallon door bin.
1 door bin with transparent front flap.

Temperature controlled drawer

Net volume 0.9 cu. ft.
No-frost technology.
1 continuous, fully extendable
temperature controlled drawer close to
32°F with transparent front, manually
controllable.

Freezer compartment

Net volume 5.8 cu. ft.
(164 liters).
No-frost technology with fast freezing.
Temperature adjustable from 7 °F to -9
°F (-14 °C to -25 °C).
2 fully extendable drawers.
Interior lighting with two spot lights.

Ice dispenser

Integrated automatic ice maker in the
freezer compartment, with fixed water
connection.
Ice maker can be switched off
independently.
Ice cube production approx. 3.1 lb (1.4
kg)/24 h.
Removable ice storage bin with approx.
6.6 lb (3 kg) capacity.

Planning notes

Flat hinge.
Door hinge right, reversible.
Door opening angle of 115°, optional
90° door stop.
Max. door panel weight:
Door 77 lb.

Product Features

Multi-Flow Air Tower

Yes

SUPERCOOL

Yes

SUPERFREEZE

No

Carbon Air Filter

No

Temperature Controlled Drawer

No

Humidity Control Drawer

Yes

Number of Door Bins - Refrigerator

1

Adjustable Door Bins - Refrigerator

No

Tilt-Out Door Bins - Refrigerator

Yes

Gallon Storage Bins

1

Number of Shelves - Refrigerator

3

Door Hinge

Right reversible

Adjustable Shelves - Refrigerator

2

Number of Shelves - Freezer

Reversible Door Hinge

Yes

Adjustable Shelves - Freezer

No

Consumption and connection features

UPC code

825225899914

Color / Material housing

Colour.Material door

Panel ready

Not possible

Silence level (dBA)

41

Watts (W)

588

Current (A)

15

Volts (V)

120

Frequency (Hz)

60

Total annual energy consumption (kWh)

451.87

Energy Star® qualified

Yes

Approval certificates

ETL, ETL C

Power Cord Length (in)

78 3/4"

Required cutout size (HxWxD) (in)

84" x 36" x 24 3/4"

Appliance Width (in)

35 3/4"

Height (in)

83 3/4 "

Depth (in)

24"

Capacity in 0.75l (bordeaux bottles)

Total unit gross capacity (cu. ft.) - AHAM

20

Product packaging dimensions

(HxWxD) (in)

88.97 x 39.37 x 29.25

Refrigerator Gross capacity (cu. ft.)

14

Freezer Gross capacity (cu ft)

6

Net weight (lbs)

486

Gross weight (lbs)

526

SKU

RB492701

2013-11-06

Page 1

Shut-off valve for water connection
must be planned next to the appliance
and always be accessible.

If the water pressure exceeds 116 psi,
connect pressure relief valve between
water tap and hose set.

Cold water connection required.

Electrical location 6" above ground in
lower left corner of unit.

Water pressure 29 to 116 psi.

Consumption data

Energy consumption 1.238 kwh/24 h.

Noise level 41 dB.

Rating

Total rating 0.588 kW.

Total Amps: 15 A.

120 V / 60 Hz

Connecting cable 78 3/4" with plug.

Supply hose 118" with 3/4" connection.

Page 2

