



Color Variants

RC472705
With fresh cooling 32 °F
Fully integrated, panel ready

Optional accessories

RA430100
Storage container with transparent lid, anthracite.

Installation Accessories

RA421713
Stainless steel door panel with handle
RA423140
RA425110
Long stainless steel door handle
RA428713
Stainless steel door panel, handleless
RA460000
Installation kit for side-by-side installation (for connecting any two columns)
RA460012
RA460020
Connecting element for vertically split appliance fronts (for a flush front)
RA464711
Ventilation grill, stainless steel

RC472705
400 series refrigeration column
With fresh cooling 32 °F
Fully integrated, panel ready
Niche width 30" (76.2 cm)

Stainless steel interior with solid anthracite aluminium elements
 Warm white and glare-free LED light spots
 Opening assist for door with two options: 1. Push-to-open function for integration into handleless furniture front 2. Pull-to-open function to facilitate opening the door using a handle
 The drawers in the RC and RF models are positioned at the same height.
 With side-by-side installation, the glass shelves and door racks can be aligned on the same level
 Flat stainless steel inner door, full-length
 Almost invisible rail system for shelves and door racks for flexible positioning
 Solid anthracite aluminium door racks
 1 fresh cooling drawer 32 °F with temperature control from 32 °F to 37 °F and one fresh cooling drawer with manually adjustable humidity
 TFT touch display
 Net volume 16.8 ft3 cu.ft. (475) litres
 Energy Star certified

Operation

TFT touch display operation.
 Clear text display in 44 languages.

Technical Features

Dynamic cold air distribution with Multi-Flow Air System.
 Automatic defrosting with defrost water evaporation.
 Cushioned door closing system.
 Activated charcoal air filter.
 Sabbath mode certified by Star-K.
 When rest mode is active, the appliance can only be opened using a handle.
 Open-door and malfunction warning system.
 Home network integration for digital services (Home Connect) wireless via WiFi.
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Cooling compartment

No-Frost technology with fast cooling.
 Temperature adjustable from 35 °F to 46 °F.
 4 safety glass shelves, white glass, 3 of which are individually adjustable in height.
 1 shallow, fully extendable drawer with transparent front.
 Cushioned closing system.
 4 brilliant LED light spots with warm white, glare-free light within cooling area and drawers.
 Flat door rail system with fully flexible positioning of door racks.
 4 height-adjustable door racks, 1 of which is extra deep.
 Net volume 406 l liters.

Fresh cooling 32 °F

1 large, fully extendable fresh cooling 32 °F drawer with transparent front, illuminated.
 Cushioned closing system.
 Temperature control via central TFT display, temperature can be adjusted from 30 °F to 38 °F.

Product Features

Multi-Flow Air Tower

Yes

SUPERCOOL

Yes

SUPERFREEZE

No

Carbon Air Filter

No

Temperature Controlled Drawer

No

Humidity Control Drawer

No

Number of Door Bins - Refrigerator

4

Adjustable Door Bins - Refrigerator

No

Tilt-Out Door Bins - Refrigerator

No

Gallon Storage Bins

1

No. of shelves in fridge

4

Door Hinge

Right reversible

Adjustable Shelves - Refrigerator

3

Number of Shelves - Freezer

Reversible Door Hinge

Yes

Adjustable Shelves - Freezer

No

Consumption and connection features

UPC code

825225961079

Color / Material housing

Variant color

Not applicable

Panel ready

Not possible

Silence level (dBA)

40

Watts (W)

350

Current (A)

10

Volts (V)

110-120

Frequency (Hz)

60

Total annual energy consumption (kWh)

279.1

Energy Star® qualified

No

Approval certificates

CSA

Power Cord Length

139 1/3"

Required cutout size (HxWxD) (in)

84" x 30" x 24 3/4"

Appliance Width (in)

29 3/4"

Height (in)

83 3/4 "

Depth (in)

24"

Capacity in 0.75l (bordeaux bottles)

Total unit gross capacity (cu. ft.) - AHAM

16.8

Product packaging dimensions

(HxWxD) (in)

88.97 x 33.46 x 29.33

Refrigerator Gross capacity (cu. ft.)

16.8

Freezer Gross capacity (cu ft)

Net weight (lbs)

369.000

Gross weight (lbs)

405.000

SKU

RC472705

2020-11-05

Page 1

Ideal for meat, fish and poultry.
 Net volume 69 litres.

Temperature controlled drawer

1 fully extendable fresh cooling drawer with transparent front, illuminated.
 Cushioned closing system.
 Humidity can be adjusted manually.
 Ideal for fruit and vegetables.

Consumption data

Energy consumption 279.08 kWh/year.
 Noise level 40 dB (re 1 pW).

Planning notes

Flat hinge.
 Door hinge right, reversible.
 Door opening angle of 115°, fixable at 90°.
 Max. door panel weight: 53 lbs. (24 kg).

Rating

Total rating 1.079 kWh/24 h.
 Total Amps: 10 A.
 Connecting cable 118" (3.0 m), detachable.

RC472705
400 series refrigeration column
With fresh cooling 32 °F
Fully integrated, panel ready
Niche width 30" (76.2 cm)
2020-11-05
Page 2

