

Dual Fuel Range 30", 4 Burners (LPG)

Professional

This 30" Fisher & Paykel freestanding range has four high power gas burners that give you precise control from a rapid boil to a gentle simmer.

Stainless Steel



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 W fisherpaykel.com

Dimensions

Depth	29 1/8″
Height	35 3/4 - 36 3/4"
Width	29 7/8"

Features & Benefits

Cooktop power

Sealed Dual Flow Burners[™] deliver cooktop power up to 22,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white – heating up; orange – temperature reached; red – self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

FISHER & PAYKEL

Handle option

Customise your Professional Fisher & Paykel kitchen appliance to suit your kitchen style by purchasing our square handle option.

Specifications

Gas Cooktop- Sealed range top

Vent trim included

Accessories

BGRV2-3030H	Combustible situation (Sold seperately)
600	Minimum CFM
BGRV2-3030 / BGRV2-1230	Non combustible situation (Sold
BGRV2-30307 BGRV2-1230	seperately)
VS30 / ES30 -30" Pro /	Recommended hood (Sold seperately)
Traditional Hood	Recommended nood (Sold seperately)
AH-R30	Square handle option (Sold seperately)
	Cleaning
•	Dishwasher proof trivets
•	Main oven- Concealed Element
•	Main oven- Self cleaning
	Controls
•	Main oven- Electronic Oven Control
•	Main oven- Internal light
•	Metal illuminated dials

Date: 15.05.2018 > 1

Flat vent trim

SPEC SHEET > RDV2-304-L_N > Dual Fuel Range 30", 4 Burners (LPG)

Cooktop performance	
Max burner power	19000 BTU
Power back left	13000 BTU
Power back right	13000 BTU
Power front left	19000 BTU
Power front right	15000 BTU
Sealed Dual Flow Burners™	4
Simmer on all burners	140 °F
Total cooktop power	60000 BTU
Gas requirements	
Fitting and pipe	1/2 NPT, min. 5%" # flex line
Supply Pressure	LPG Pressure 11" to 14" W.C
Oven features	
Main oven- Broil pan	•
Oven functions	
Main oven functions	6
Main oven- Bake	•
Main oven- Broil	•
Main oven- Clean	•
Main oven- Convection Bake	•
Main oven- Convection Broil	•
Main oven- True Convection	•

3500 W 4000 W 5 4 cu ft 2500 W 3.3 cu ft 4 cu ft 4 wire 30
4000 W 5 4 cu ft 2500 W 3.3 cu ft 4 cu ft 4 wire
5 4 cu ft 2500 W 3.3 cu ft 4 cu ft 4 wire
4 cu ft 2500 W 3.3 cu ft 4 cu ft 4 wire
2500 W 3.3 cu ft 4 cu ft 4 wire
3.3 cu ft 4 cu ft 4 wire
4 cu ft 4 wire
4 wire
30
50
60
120 - 240
29 1/8 "
35 3/4 - 36 3/4 "
29 7/8 "
3
Professional
71373

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © © Fisher & Paykel Appliances Ltd 2018

Other product downloads available at fisherpaykel.com

fisherpaykel.com