

Dual Fuel Range 36", 6 Burners (LPG)

Professional

This 36" Fisher & Paykel freestanding range has six high power burners and a large oven that can fit full size baking sheets.

Stainless Steel



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 W fisherpaykel.com

Dimensions

Depth	29 1/8″
Height	35 3/4 - 36 3/4"
Width	35 7/8"

Features & Benefits

Cooktop power

Sealed Dual Flow Burners[™] deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white – heating up; orange – temperature reached; red – self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

FISHER & PAYKEL

Handle option

Customise your Professional Fisher & Paykel kitchen appliance to suit your kitchen style by purchasing our square handle option.

Specifications

Accessories

ble situation (Sold seperately) BGRV2-3036H
CFM 600-1,200
ustible situation (Sold BGRV2-3036 / BGRV2-1236
)
VS36 / VS1236 -36" Pro nded hood (Sold seperately)
Hood
ndle option (Sold seperately) AH-R36
• •
- Concealed Element •
- Self cleaning •
- Electronic Oven Control •
- Internal light •
inated dials

Gas Cooktop- Sealed range top	•
Vent trim included	Flat vent trim

Cooktop performance	
Max burner power	19000 BTU
Power back centre	13000 BTU
Power back left	13000 BTU
Power back right	13000 BTU
Power front centre	15000 BTU
Power front left	19000 BTU
Power front right	19000 BTU
Sealed Dual Flow Burners™	6
Simmer on all burners	140 °F
Total cooktop power	92000 BTU
Gas requirements	
Fitting and pipe	½ NPT, min. %" # flex line
Supply Pressure	LPG Pressure 11" to 14" W.C
Oven features	
Main oven- Large broil pan	•
Oven functions	
Main oven functions	6
Main oven- Bake	•
Main oven- Broil	•
Main oven- Clean	•
Main oven- Convection Bake	•
Main oven- Convection Broil	•
Main oven- True Convection	•

4600 W
4600 W
4000 W
5
4.8 cu ft
2500 W
3.8 cu ft
4.8 cu ft
4 wire
30
60
120 - 240
29 1/8 "
35 3/4 - 36 3/4 "
35 7/8 "
3
Professional

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © © Fisher & Paykel Appliances Ltd 2018

Date: 15.05.2018 > 2

Other product downloads available at fisherpaykel.com

fisherpaykel.com