

RDV2-485GD-N N

Dual Fuel Range 48", 5 Burners with Griddle

Professional

This 48" Fisher & Paykel dual fuel freestanding range gives you cooking flexibility with five high power burners, a griddle plate and two oven cavities.

Stainless Steel



Dimensions

29 1/8" Depth Height 35 3/4 - 36 3/4" Width 47 7/8"

Features & Benefits

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area - perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

Handle option

Customise your Professional Fisher & Paykel kitchen appliance to suit your kitchen style by purchasing our square handle option.

Specifications

BGRV2-3048F
1,200
BGRV2-3048 / BGRV2-1248
BORV2-3040 / BORV2-1240
VS48-48" Pro Hood
AH-R48
•
•
•
•
•
•
•
•

Vent trim included

Gas Cooktop- Sealed range top

Flat vent trim

Cooktop performance	
Max burner power	23500 BTU
Power back left	18500 BTU
Power back right	18500 BTU
Power centre	23500 BTU
Power front left	18500 BTU
Power front right	18500 BTU
Power griddle	24000 BTU
Sealed Dual Flow Burners $^{\text{\tiny TM}}$	5
Simmer on all burners	140 °F
Total cooktop power	121500 BTU
Gas requirements	
Fitting and pipe	½ NPT, min. 5/8" # flex line
Supply Pressure	NG Pressure 6" to 9" W.C
Oven features	
Main oven- Large broil pan	•
Secondary Oven- 3/4 extention racks	2

Oven functions	
Main oven functions	6
Main oven- Bake	•
Main oven- Broil	•
Main oven- Clean	•
Main oven- Convection Bake	•
Main oven- Convection Broil	•
Main oven- True Convection	•
Secondary Oven- Bake	•
Secondary Oven- Broil	•
Secondary Oven- Proof	•
Secondary oven functions	3
Oven performance	
Main oven- Bake	4600 W
Main oven- Broil	4000 W
Main oven- Shelf positions	5
Main oven- Total Capacity (AHAM)	4.8 cu f
Main oven- True Convection	2500 W
Main oven- Usable Capacity (AHAM)	3.8 cu ft
Secondary Oven- Bake	2450 W
Secondary Oven- Broil	3600 W
Secondary Oven- Capacity total (AHAM)	2.1 cu f
Secondary Oven- Capacity usable (AHAM)	1.8 cu f
Secondary Oven- Shelf positions	5
Total oven capacity	6.9 cu f

Power requirements	
Electric circuit	4 wire
Rated current	50
Supply frequency	60
Supply voltage	120 - 240
Product dimensions	
Depth (excluding handle and dials)	29 1/8 "
Height (excluding vent trim)	35 3/4 - 36 3/4 "
Width	47 7/8 "
Safety	
Full extension telescopic racks	3
Style And Series	
Product Style	Professional
SKU	71360
The product dimensions and specifications in this and model. Under our policy of continuous improv	

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © © Fisher & Paykel Appliances Ltd 2018

Other product downloads available at fisherpaykel.com fisherpaykel.com