

RDV2-486GD-L_N

Dual Fuel Range 48", 6 Burners with Griddle (LPG)

Professional

This 48" Fisher & Paykel dual fuel freestanding range gives you cooking flexibility with six high powered burners, a griddle and two oven cavities.

Stainless Steel



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support T 1.888.936.7872 W fisherpaykel.com

Dimensions

Depth	29 1/8″
Height	35 3/4 - 36 3/4"
Width	47 7/8"

Features & Benefits

Cooktop power

Sealed Dual Flow Burners[™] deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Consistent broiling

The Dual Fuel Range broiler provides an even heat that covers a very large surface area — perfect for browning a fully loaded oven tray.

Easy to clean

The Dual Fuel Range oven has a self-cleaning function and removable side racks. The cooktop has sealed burners and an encapsulated cooking surface with a commercial-style stainless steel finish.

Instant visibility

Control dials have halo-illumination glowing white – heating up; orange – temperature reached; red – self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

FISHER & PAYKEL

- Handle option

Customise your Professional Fisher & Paykel kitchen appliance to suit your kitchen style by purchasing our square handle option.

Specifications

Accessories

Combustible situation (Sold seperately)	BGRV2-3048H
Minimum CFM	1,200
Non combustible situation (Sold	BGRV2-3048 / BGRV2-1248
seperately)	BGRV2-3046 / BGRV2-1246
Recommended hood (Sold seperately)	VS48-48" Pro Hood
Square handle option (Sold seperately)	AH-R48
Cleaning	
Dishwasher proof trivets	•
Main oven- Concealed Element	•
Main oven- Self cleaning	•
Secondary Oven- Concealed Element	•
Controls	
Main oven- Electronic Oven Control	•
Main oven- Internal light	
Metal illuminated dials	•
Secondary Oven- Electronic Oven Control	•
Secondary Oven- Internal light	•

Cooktop features

Gas Cooktop- Sealed range top

Cooktop performance	
Max burner power	19000 BTU
Power back centre	13000 BTU
Power back left	13000 BTU
Power back right	13000 BTU
Power front centre	15000 BTU
Power front left	19000 BTU
Power front right	15000 BTU
Power griddle	15000 BTU
Sealed Dual Flow Burners™	6
Simmer on all burners	140 °F
Total cooktop power	103000 BTU
Gas requirements	
Fitting and pipe	½ NPT, min. 5⁄8″ # flex line
Supply Pressure	LPG Pressure 11" to 14" W.C

Oven features

Main oven- Large broil pan	
Secondary Oven- 3/4 extention racks	
Secondary Oven- Broil pan	

I	Main oven functions	6
I	Main oven- Bake	•
I	Main oven- Broil	•
I	Main oven- Clean	•
I	Main oven- Convection Bake	•
I	Main oven- Convection Broil	•
I	Main oven- True Convection	•
!	Secondary Oven- Bake	•
!	Secondary Oven- Broil	•
!	Secondary Oven- Proof	•
!	Secondary oven functions	3
	Oven performance	
	Oven performance Main oven- Bake	4600 W
I		4600 W 4000 W
	Main oven- Bake	
	Main oven- Bake Main oven- Broil	4000 W
	Main oven- Bake Main oven- Broil Main oven- Shelf positions	4000 W 5
	Main oven- Bake Main oven- Broil Main oven- Shelf positions Main oven- Total Capacity (AHAM)	4000 W 5 4.8 cu ft
	Main oven- Bake Main oven- Broil Main oven- Shelf positions Main oven- Total Capacity (AHAM) Main oven- True Convection	4000 W 5 4.8 cu ft 2500 W
	Main oven- Bake Main oven- Broil Main oven- Shelf positions Main oven- Total Capacity (AHAM) Main oven- True Convection Main oven- Usable Capacity (AHAM)	4000 W 5 4.8 cu ft 2500 W 3.8 cu ft
	Main oven- Bake Main oven- Broil Main oven- Shelf positions Main oven- Total Capacity (AHAM) Main oven- True Convection Main oven- Usable Capacity (AHAM) Secondary Oven- Bake	4000 W 5 4.8 cu ft 2500 W 3.8 cu ft 2450 W
	Main oven- Bake Main oven- Broil Main oven- Shelf positions Main oven- Total Capacity (AHAM) Main oven- True Convection Main oven- Usable Capacity (AHAM) Secondary Oven- Bake Secondary Oven- Broil	4000 W 5 4.8 cu ft 2500 W 3.8 cu ft 2450 W 3600 W
	Main oven- Bake Main oven- Broil Main oven- Shelf positions Main oven- Total Capacity (AHAM) Main oven- True Convection Main oven- Usable Capacity (AHAM) Secondary Oven- Bake Secondary Oven- Broil Secondary Oven- Capacity total (AHAM)	4000 W 5 4.8 cu ft 2500 W 3.8 cu ft 2450 W 3600 W 2.1 cu ft
	Main oven- Bake Main oven- Broil Main oven- Shelf positions Main oven- Total Capacity (AHAM) Main oven- True Convection Main oven- Usable Capacity (AHAM) Secondary Oven- Bake Secondary Oven- Broil Secondary Oven- Capacity total (AHAM) Secondary Oven- Capacity usable (AHAM)	4000 W 5 4.8 cu ft 2500 W 3.8 cu ft 2450 W 3600 W 2.1 cu ft 1.8 cu ft

Oven functions

٠

2

ο

Power requirements

Electric circuit	4 wire
Rated current	50
Supply frequency	60
Supply voltage	120 - 240
Product dimensions	
Depth (excluding handle and dials)	29 1/8 "
Height (excluding vent trim)	35 3/4 - 36 3/4 "
Width	47 7/8 "
Safety	
Full extension telescopic racks	3
Style And Series	
Product Style	Professional
SKU	71363

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © © Fisher & Paykel Appliances Ltd 2018

Other product downloads available at fisherpaykel.com

fisherpaykel.com