



#### Color Variants

RF461705  
Fully integrated, panel ready  
Niche width 24" (61 cm)

#### Optional accessories

RA448220  
Ice storage container, small.  
RA450022

#### Installation Accessories

RA421615  
Stainless steel door panel with handle  
RA423140  
RA425110  
Long stainless steel door handle  
RA428615  
Stainless steel door panel, handleless  
RA460012  
RA460020  
Connecting element for vertically split  
appliance fronts (for a flush front)  
RA464616  
Ventilation grill, stainless steel

RF461705  
Vario freezer 400 series  
Fully integrated, panel ready  
Niche width 24" (61 cm)

Stainless steel interior with solid anthracite aluminium elements  
Warm white and glare-free LED light spots

Opening assist for door with two options: 1. Push-to-open function for integration into handleless furniture front 2. Pull-to-open function to facilitate opening the door using a handle

The drawers in the RC and RF models are positioned at the same height.  
With side-by-side installation, the glass shelves and door racks can be aligned on the same level

Material and aesthetics of interior as for RC model - Glass shelves - Solid anthracite aluminium door racks  
Flat stainless steel inner door, full-length

Almost invisible rail system for shelves and door racks for flexible positioning  
Integrated automatic ice maker with fixed water connection  
TFT touch display  
Net volume 12.2 ft<sup>3</sup> cu.ft. (345) litres  
Energy Star certified

#### Operation

TFT touch display operation.  
Clear text display in 44 languages.

#### Technical Features

Dynamic cold air distribution with Multi-Flow Air System.  
Automatic defrosting with defrost water evaporation.  
Cushioned door closing system.  
Sabbath mode certified by Star-K.  
When rest mode is active, the appliance can only be opened using a handle.  
Open-door and malfunction warning system.  
Home network integration for digital services (Home Connect) wireless via WiFi.  
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

#### Freezer compartment

No-frost technology with fast freezing at -22 °F.  
Temperature adjustable from 3 °F to -11 °F.  
4-star freezer compartment.  
Freezing capacity 6.3 kg/24 h.  
4 safety glass shelves, white glass, 3 of which are individually height adjustable.  
2 fully extendable drawers with transparent front.  
Brilliant LED light spots with warm white, glare-free light.  
Flat door rail system with fully flexible positioning of door racks.  
4 height-adjustable door racks.

#### Ice dispenser

Integrated automatic ice maker in the freezer compartment, with fixed water connection.  
Particle filter for water inlet, integrated in ventilation grille area.  
Saturation indicator shown in TFT touch display.  
Ice maker can be switched off independently.

#### Product Features

Multi-Flow Air Tower  
Yes  
Number of compressors  
1  
Number of independent cooling systems  
1  
Eco Mode  
Yes

#### SUPERFREEZE

No  
Number of Door Bins - Freezer  
4

#### Adjustable Door Bins - Freezer

No

#### Tilt-Out Door Bins - Freezer

No

#### Number of Shelves - Freezer

3

#### Adjustable Door Bins - Freezer

No

#### Shelf Material - Freezer

Safety glass

#### Door Hinge

Left reversible

#### Reversible Door Hinge

Yes

#### Consumption and connection features

UPC code  
825225960928

Variant color  
Not applicable

#### Panel ready

#### Installation Type

N/A

#### Silence level (dBA)

42

#### Watts (W)

350

#### Current (A)

10

#### Volts (V)

110-120

#### Frequency (Hz)

60

#### Total annual energy consumption (kWh)

435.0

#### Energy Star® qualified

No

#### Approval certificates

CSA

#### Power Cord Length

139 1/3"

#### Plug type

120V-3 prong

#### Appliance dimensions (h x w x d) inch

83 3/4 " x 23 3/4 " x 24"

#### Required cutout size (HxWxD) (in)

84" x 24" x 24 3/4"

#### Appliance Width (in)

23 3/4 "

#### Height (in)

83 3/4 "

#### Depth (in)

24"

#### Product packaging dimensions

(HxWxD) (in)  
88.97 x 26.77 x 29.72

#### Total unit gross capacity (cu. ft.) - AHAM

12.2

#### Net weight (lbs)

323.000

#### Gross weight (lbs)

355.000

#### 2020-11-04

Page 1

Ice cube production approx. 2.9 lb (1.3 kg)/24 h.

Removable ice storage container with approx. 6.6 lbs. (2.5 kg) capacity.

#### Consumption data

Energy consumption 435 kWh/year.  
Noise level 42 dB (re 1 pW).

#### Planning notes

Flat hinge.  
Door hinge left, reversible.  
Door opening angle of 115°, fixable at 90°.

For installation with a door opening angle of 90° the ice storage container must be exchanged for the small ice storage container (RA 448220). This must be done prior to fixing the door.  
Max. door panel weight 90 lbs (41 kg).  
Shut-off valve for water connection must be planned next to the appliance and always be accessible.

If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.

#### Rating

Total rating 1.079 kWh/24 h.  
Total Amps: 10 A.  
Connecting cable 118" (3.0 m), detachable.  
Cold water connection required.  
Electrical location 6" above ground in lower left corner of unit.  
Supply hose 47,2 INCH (1.2 m) with 1/4" male compression fitting (standard icemaker connector).  
Water pressure 29 to 116 psi.

