# Gas Range, 30", 4 Burners

#### Series 7 | Professional

Stainless Steel | Natural gas



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 22,500 BTU, for seriously fast boiling
- Gas oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

## DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	29 7/8″
Depth	29 1/8″

## **FEATURES & BENEFITS**

#### Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 22,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

#### Cooking flexibility

<>

#### Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

#### Easy to clean

<>

#### **Total control**

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

## SPECIFICATIONS

Accessories	
Square handle option	AH-R30
Burner ratings	
Maximum burner power	22500 BTU
Power back left	18500BTU

## FISHER & PAYKEL

Power back right	18500BTU
Power front left	22500BTU
Power front right	18500BTU
Total cooktop power	78000 BTU
Capacity	
Shelf positions	:
Shelf positions	5
Cleaning	
Easy clean porcelain basepan	
Controls	
Electric circuit	3 wire
Metal illuminated dials	
Gas Requirements	
Fitting and pipe	½ NPT, min. %″ 🛛 flex line
Supply Pressure (natural gas)	6" to 9" W.C
Oven features	
Broil pan	
Electronic oven control	
Full extension telescopic	
Infrared Broiler	
Internal light	
Titanium coated, illuminated	

Bake

#### QUICK REFERENCE GUIDE > RGV3-304-N

Broil	•
Convection bake	•
Number of functions	4
Slow cook	•
Oven performance	
Bake power	21,000 BTU
Broil power	18,500 BTU
Power requirements	
Amperage	15A
Rated current	15A
Supply frequency	60Hz
Product dimensions	
Depth	29 1/8″
Height	35 3/4 - 36 3/4"
Width	29 7/8"
Rangetop features	
Sealed Dual Flow Burners™	4
Sealed range top	•

## Recommended Back Guards Ventilation

Vent trim included

Combustible situation	BGRV3-3030H
Non combustible situation	BGRV2-3030 / BGRV2-1230
Recommended hood	HCB30-6_N (Professional

## Safety

ADA compliant	•
Full extension telescopic	•
SKU	82004

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

## Other product downloads available at fisherpaykel.com



≁

Installation Guide

24/7 A PEAC 24 Hour 11888 9

A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com