QUICK REFERENCE GUIDE > RGV3-366-N

# Gas Range, 36", 6 Burners

Series 7 | Professional

Stainless Steel | Natural gas



Professional style with power. 23,500 BTU gas burners paired with a large capacity gas oven.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- Gas oven with 5.3 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

## **DIMENSIONS**

Height	35 3/4 - 36 3/4'
Width	35 7/8"
Depth	29 1/8'

#### **FEATURES & BENEFITS**

#### Generous capacity

Featuring a generous total capacity of 5.3 cu ft, with enough room to fit a 32 lb turkey and full-sized baking sheets.

#### Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

## Cooking flexibility

<>

## Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

#### Easy to clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

#### Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

## **SPECIFICATIONS**

#### Accessories

Square handle option AH-R36

Burner ratings	
Maximum burner power	23500 BTU
Power back centre	18500BTU
Power back left	18500BTU
Power back right	18500BTU
Power front centre	18500BTU
Power front left	23500BTU
Power front right	23500BTU
Total cooktop power	121000 BTU

## Capacity

Shelf positions	;
Shelf positions	

#### Controls

Clastuia aivavit

Electric circuit	2 Mile	
Metal illuminated dials		
rietai iliurriiriatea diais		

## **Gas Requirements**

Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (natural gas)	6" to 9" W.0

#### Oven features

Broil pan	•
Electronic oven control	•
Full extension telescopic	•
Infrared Broiler	•
Internal light	

QUICK REFERENCE GUIDE > RGV3-366-N Date: 07.04.2022 > 2

Titanium coated, illuminated	•
Oven functions	
Bake	•
Broil	•
Convection bake	•
Number of functions	4
Slow cook	•
Oven performance	
Bake power	28,000 BTU
Broil power	18,500 BTU
Power requirements	
Amperage	15A
Rated current	15A
Supply frequency	60Hz
Product dimensions	
Depth	29 1/8"
Height	35 3/4 - 36 3/4"
Width	35 7/8"
Rangetop features	
Sealed Dual Flow Burners™	6
Sealed range top	•
Vent trim included	•
Recommended Back Guards Ventilation	
Combustible situation	BGRV3-3036H

Non combustible situation	BGRV2-3036 / BGRV2-1236
Recommended hood	HCB36-6_N (36" Professional
Safety	
ADA compliant	•
Full extension telescopic	•
SKU	82002

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

## Other product downloads available at fisherpaykel.com



User Guide



Installation Guide

