

CHIMNEY WALL HOODS WITH STANDARD VENTILATOR

RVCH330 – 30" WIDE

RVCH336 – 36" WIDE



Features and Functions

- 460 CFM interior-power ventilator ships standard
- Variable-speed control for custom venting
- Halogen lights for better visibility and efficiency
- Dimmer on lights allows custom lighting – separate on/off switch allows consumer to leave dimmer in favorite position
- Heat sensor activates ventilator to full power when cooking temperatures reach uncomfortable levels
- Recirculating kit with air-purifying charcoal filters available and sold separately if exterior ducting is not desirable
- Adjustable duct cover comes standard with product

Easy Cleanup

- Mesh filters made entirely of stainless steel for durability and long life; efficiently remove grease and heated vapors from the air
- Dishwasher-safe filters are easily removed for quick cleaning
- Design of low-profile filter system means less interior hood space to be cleaned
- Interior of rangehood canopy has stainless steel liner for increased rigidity, seamless appearance, and easy cleaning

Installation Accessories

- Recirculating kit for 30"W. Hood (DRK30)
- Recirculating kit for 36"W. Hood (DRK36)



Wall Hood with Standard Ventilator 30" and 36" Widths

Finishes

- Available in Stainless Steel (SS), Black (BK), and White (WH)



Warranty Highlights

- Three-year full – complete product
- Ninety-day full – cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited – stainless steel exterior
- Five-year limited – all ventilator motors



DESCRIPTION	CHIMNEY WALL HOODS WITH STANDARD VENTILATOR									
	DUCT COVERS			NUMBER OF LIGHTS	NUMBER OF FILTERS	RECOMMENDED DUCT SIZE		MAXIMUM AMPS		
	WIDTH	DEPTH	HEIGHT			INTERIOR	EXTERIOR	INTERIOR	IN-LINE	EXTERIOR
CHIMNEY HOODS WITH STANDARD INTERIOR-POWER VENTILATOR – 24" DEEP										
A 460 CFM BLOWER IS SHIPPED WITH HOOD										
30" W. RVCH330	16"	12"	18"– 30"	2	2	7"	–	5.6	5.6	N/A
36" W. RVCH336	16"	12"	18"– 30"	2	2	7"	–	5.6	5.6	N/A



Viking Range, LLC | 1-888-845-4641 or 662-455-1200

For detailed product information, model numbers, or to request a quote visit vikingrange.com

© 2013 Viking Range, LLC | Specifications subject to change without notice.