

# GAS SELF-CLEAN RANGE

## RVGR330-5B – 30" WIDE



### Features and Functions

- Wide variety of BTU ratings to accommodate all types of surface cooking needs – including a fifth burner
  - Left front – 18,000 BTU
  - Left rear – 8,000 BTU
  - Center – 9,000 BTU
  - Right front – 18,000 BTU
  - Right rear – 12,000 BTU
- Sealed burners with porcelainized, cast-iron burner caps
- **Exclusive** – SureSpark™ Ignition System
  - Automatic electric spark ignition/re-ignition; surface burners light at any position on the knob and re-light if extinguished, even on lowest setting
- Large-capacity oven has six porcelain-coated rack supports and comes standard with one TruGlide™ full extension oven rack and two standard racks.
- High performance cooking modes include Natural Airflow Bake, Convection Bake, Broil, Convection Broil, Convection Dehydrate, and Convection Defrost
- All convection functions utilize the ProFlow™ Convection Air Baffle; specifically designed to ensure balanced air flow for even heat distribution
- **Exclusive** – combination of single 30,000 BTU U-shaped burner and broiler with SureSpark™ Ignition System

- 15,000 BTU broiler provides intense searing heat for broiling applications
- Two halogen oven lights for excellent visibility throughout oven cavity
- Shipped standard with island trim
- Accessory portable griddle/grill (RDPGD) available for use over center burner

### Easy Operation and Cleanup

- Extremely large self-clean convection oven
- Permanently sealed burners – spills cannot enter the one-piece, tooled and porcelainized burner box
- Durable metal die-cast knobs with child-proof, push-to-turn safety feature
- Customer-removable knobs, grates, and burners/caps for easy cleaning
- Continuous grate design for easy movement of pots and pans

### Installation Accessories

- 6" high backguard (RD30BG6)
- High shelf (RD30HS24)
- Countertop side trim (P24CST)
- Countertop rear trim (P30CRT)
- Curb base and custom curb base front (P30CBF4)
- LP conversion kit (RDLPKR)

### Finishes

- Available in Stainless Steel (SS), Black (BK), and White (WH)



### Warranty Highlights

- Three-year full – complete product
- Ninety-day full – cosmetic parts such as glass, painted items, and decorative items
- Lifetime limited – stainless steel exterior
- Ten-year limited – porcelain oven
- Five-year limited – surface/tube burners



30" Wide Gas Self-Clean Range  
(Shown with optional 6" H. backguard)

DESCRIPTION	GAS SELF-CLEAN 30" WIDE RANGE
	RVGR330-5B
Overall Width	29 7/8" (75.9 cm)
Overall Height	To top of side trim – 35 7/8" (91.1 cm) minimum; 37" (94.0 cm) maximum Legs adjust – 1 1/8" (2.9 cm)
Overall Depth from Rear	To front of side panel – 25" (63.5 cm) To front of door – 25 3/4" (65.4 cm) To front of control panel – 27 1/8" (68.9 cm) To end of knobs – 29" (73.7 cm)
Additions to Overall Height	To top of island trim – add 0" (0.0 cm) To top of 6" h. backguard – add 6" (15.2 cm) To top of high shelf – add 18 3/16" (46.2 cm)
Gas Requirements	Ships Natural or LP/Propane; Field convert with conversion kit (purchased separately); accepts standard residential 1/2" (1.3 cm) ID gas service line.
Gas Manifold Pressure	Natural 5.0" W.C.P./ Liquid Propane L/P 10.0" W.C.P.
Electrical Requirements	120VAC/60Hz; 4 ft. (121.9 cm), 3-wire cord with grounded 3-prong plug attached to unit
Maximum Amp Usage	.74 amps
Surface Burner Rating Natural/LP	Left Front: 18,000 BTU Nat./15,800 BTU LP/Propane (5.3 kW Nat./4.7 kW LP/Propane) Left Rear: 8,000 BTU Nat./6,500 BTU LP/Propane (2.3 kW Nat./1.9 kW LP/Propane) Center: 9,000 BTU Nat./8,000 BTU LP/Propane (2.7 kW Nat./2.3 kW LP/Propane) Right Front: 18,000 BTU Nat./15,800 BTU LP/Propane (5.0 kW Nat./4.4 kW LP/Propane) Right Rear: 12,000 BTU Nat./11,000 BTU LP/Propane (3.5 kW Nat./3.2 kW LP/Propane)
Oven Interior Width	23" (58.4 cm)
Oven Interior Height	16 1/8" (40.9 cm)
Oven Interior Depth	Overall – 18 3/4" (47.6 cm) AHAM* – 15 3/8" (39.1 cm)
Oven Volume	Overall – 4.0 cu. ft. AHAM* – 3.3 cu. ft.
Approximate Shipping Weight	410 lb. (184.5 kg)

\*The AHAM standard for measuring oven capacity subtracts the doorplug and convection baffle dimension from the total oven volume.

800-570-3355



Viking Range, LLC | 1-888-VIKING (845-4641) or 662-455-1200  
For detailed product information, model numbers, or to request a quote visit [vikingrange.com](http://vikingrange.com)  
© 2013 Viking Range, LLC | Specifications subject to change without notice.