



Color Variants

RW466765

Fully integrated, panel ready, with glass door

Niche width 24" (61 cm)

Optional accessories

RA430000

Screw hole cover set. 8 pieces.

RA492660

Removable shelf with oak wood frame

RA493060

Presenter in oak wood and aluminum in anthracite for single bottle display.

Installation Accessories

RA420010

Door lock

RA421616

Stainless steel door panel frame with handle

RA421617

Stainless steel door panel frame with handle

RA423140

RA425110

Long stainless steel door handle

RA428616

Stainless steel door panel frame, handleless

RA460012

Connecting element for vertically split appliance fronts (for a flush front)

RA464611

Ventilation grill, stainless steel

RW466765

400 series wine climate cabinet

Fully integrated, panel ready, with glass door

Niche width 24" (61 cm)

3 independently controllable climate zones
 Consistent temperatures with exact control from 41 °F to 68 °F
 Humidity control
 Stainless steel interior
 Fully extendable bottle trays in oak wood and solid aluminium in anthracite
 Bottle trays with hidden telescopic rails
 Warm white and glare-free LED light spots
 5 preset lighting scenarios, selectable via TFT display
 Opening assist for door with two options: 1. Push-to-open function for integration into handleless furniture front 2. Pull-to-open function to facilitate opening the door using a handle
 Low-vibration operation
 TFT touch display
 Capacity 99 bottles
 Energy Star certified

Operation

TFT touch display operation.
 Clear text display in 44 languages.

Technical Features

Dynamic cold air distribution with Multi-Flow Air System.
 Automatic defrosting with defrost water evaporation.
 Cushioned door closing system.
 Activated charcoal air filter.
 UV-protection.
 Sabbath mode certified by Star-K.
 When rest mode is active, the appliance can only be opened using a handle.
 Open-door and malfunction warning system.
 Home network integration for digital services (Home Connect) wireless via WiFi.
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Features

Capacity 99 bottles (based on 0.75/l standard bottles).
 12 bottle trays, - 9 fully extendable trays - 3 suitable for storage of Magnum bottles.
 Flexible interior configuration possible by adding or removing fully extendable bottle trays.
 Storage of up to 12 Magnum bottles with standard tray configuration (12 bottle trays).
 Space for max. 12 bottle trays.
 2 brilliant LED light spots with warm white, glare-free light in each climate zone.
 5 different lighting scenarios can be selected for individual wine presentation.
 Net volume 13.4 ft3 cu.ft.

Consumption data

Energy consumption 178.9 kWh/year.
 Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.
 Door hinge right, reversible.
 Door opening angle of 115°, fixable at 90°.
 Max. door panel weight 73 kg.

Product Features

Number of temperature zones

Range of temperature (°C)

5-20

Eco Mode

Yes

Carbon Air Filter

No

Presenter Lighting

No

Presenter Shelf

No

Type of Glass Door

2 glass panels

Number of Adjustable Shelves

0

Number of shelves

9

Bottles per Shelf

7

Door Hinge

Right reversible

Shelf Material - Refrigerator

Reversible Door Hinge

Yes

Lighting

Consumption and connection features

UPC code

825225961185

Color / Material housing

Variant color

Not applicable

Panel ready

Not possible

Installation Type

N/A

Silence level (dBA)

42

Watts (W)

350

Current (A)

10

Volts (V)

110-120

Frequency (Hz)

60

Energy consumption per Year (kWh/a) winecooler

178.9

Approval certificates

CSA

Power Cord Length

139 1/3"

Plug type

120V-3 prong

Required cutout size (HxWxD) (in)

84" x 24" x 24 3/4"

Appliance Width (in)

23 3/4"

Height (in)

83 3/4 "

Depth (in)

24"

Capacity in 0.75l (bordeaux bottles)

99

Total unit gross capacity (cu. ft.) - AHAM

Product packaging dimensions (HxWxD) (in)

88.97 x 26.37 x 29.33

Net weight (lbs)

340.000

Gross weight (lbs)

372.000

2020-11-03

Page 1

Plan a power outlet outside of the cut-out niche.

No transport/operation above 6,500 feet (2,000) sea level.

Rating

Total rating 1.079 kWh/24 h.

Total Amps: 10 A.

Connecting cable 118" (3.0 m), detachable.

