

# Viking Undercounter/Freestanding Refrigerators

## Features

- Electronic controls with digital temperature readout
  - Temperature can be adjusted from 33 to 39 degrees F (.6-3.9 degrees C); factory set at 34 degrees F (18.3 degrees C)
  - Can be displayed in either Fahrenheit or Celsius
- 5.3 cubic feet of storage
- Two full extension adjustable wire shelves
  - 75 lbs. capacity
  - Each shelf accommodates 54 12-oz. cans
  - Removable and adjustable
- Dual pane and argon filled Low 'E' energy efficient glass doors (indoor model only)
- LED display lighting
- Energy Star qualified

## Construction and Design

- Forced air cooling system
- Powerful 700 BTU compressor
- Stainless steel interior
- Stainless steel exterior cabinet
- Tru-Flush™ design allows refrigerator to fit flush into 24" deep installation cutout
- Undercounter or freestanding installation
- Self-closing door
- Door lock (outdoor model only)
- Super quiet 32-39 db sound rating
- Black kickplate (indoor model); stainless kickplate (outdoor model)
- Adjustable leveling legs

## Models

- VRCI1240G – 24"W. Professional Refrigerator w/glass door (R/L)
- FRCI1240G – 24"W. Custom Panel Refrigerator w/glass door (R/L)
- VRCO1240D – 24"W. Outdoor Refrigerator w/solid door (R/L)

## Finish and Design Options

- VRCI/VRCO models available in Stainless Steel (SS) only
- FRCI models accept custom panels

## Optional Accessories

- Professional handle kit for custom front models – PHK30SS

## Warranty Highlights

- Three-year full – covers complete unit/One-year full (Outdoor)
  - Six-year full – sealed system (Indoor only)
  - Lifetime limited – stainless steel exterior
  - 12-year limited – (Indoor only)
  - 5-year limited (Outdoor)
  - Ninety-day limited – cosmetic parts such as glass, painted items, and decorative items
- \* Warranty valid on Viking products shipped within the United States and Canada



VRCI1240G

**AiMadison**  
Your Appliance Authority™  
800-570-3355



Professional Performance for the Home™

## Basic Specifications

Description	24" W. UNDERCOUNTER/FREESTANDING REFRIGERATORS
	VRCI/FRCI/VRCO1240
<b>Overall Width</b>	23 7/8" (60.6 cm)
<b>Overall Height</b>	34 1/4" (87.0 cm)
<b>Overall Depth from Rear</b>	Without door panel: 23 5/16" (59.2 cm) To front of door panel: 24 1/16" (61.1 cm) To front of handle: 26 9/16" (67.5 cm)
<b>Cutout Width</b>	24" (61.0 cm)
<b>Cutout Height</b>	34 1/2"-35 1/2" ( 87.6-96.2 cm)
<b>Cutout Depth</b>	24" (61.0 cm)
<b>Electrical Requirements</b>	115V/60 Hz; 15 amp dedicated circuit; 5' power cord attached to product
<b>Maximum Amp Usage</b>	3.0 amps
<b>Maximum Storage Capacity</b>	5.3 cu. ft.
<b>Approximate Shipping Weight</b>	215 lbs. (98 kg)

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



Viking Range Corporation  
111 Front Street  
Greenwood, Mississippi 38930 USA

(662) 455-1200

For product information, call 1-888-VIKING1 (845-4641),  
or visit the Viking Web site at [vikingrange.com](http://vikingrange.com)



All models with standard equipment are design-certified for residential installation.

© 2011, Viking Range Corporation.

To receive the most current specification sheets, visit Dimension Express at [www.dexpress.com](http://www.dexpress.com) or call from your fax machine at (925)284-3558. Enter code #8051 for Viking Products. This will send you information on how to use the system and the corresponding model code numbers. Dimension Express customer support can be reached by email at: [support@dexpress.com](mailto:support@dexpress.com).