

# SCR610BLSD



34" x 23.63" x 23.5" (H x W x D)

Built-in undercounter commercial all-refrigerator w/SS interior, lock, and digital thermostat

### Highlights:

ETL-S listed to NSF-7 commercial standards

Stainless steel interior ensures long-lasting durability with easy cleanup

Full capacity interior can store two rows of tall bottles in an upright position

### Product Features:

Commercially approved	ETL-S listed to NSF-7 Standards for use in commercial establishments
Built-in capable	Make the best use of space by installing this unit under the counter and flush with other cabinetry
Stainless steel door	Professional finish with a matching handle
Stainless steel interior	Walls are constructed from stainless steel for added strength and easy cleanup
Factory installed lock	Keyed lock for a secure interior
Digital thermostat	Intuitive digital controls ensure easy temperature management
Reversible door	User-reversible door swing allows for more flexibility in placing the unit
Cantilevered chrome shelves	Rearrange refrigerator space to accommodate all sizes or remove shelves for simple cleanup
Tall interior	25" high interior accommodates two vertical rows of 12" tall bottles



## SCR610BLSD Specifications:

Overview	
Height of Cabinet	34.0" (86 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.38" (64 cm)
Depth with door at 90°	45.5" (116 cm)
Capacity	5.0 cu.ft. (142 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	105.0 lbs. (48 kg)
Estimated Time to Ship	3 to 5 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Refrigerator Features	
Sabbath Mode	Yes
Door Swing	RHD
Reversible	Yes
Shelf Type	Chrome
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant Type	R600a
Refrigerant Amount	0.99oz.
High Side PSI	270.0
Low Side PSI	105.0
Level Legs Qty	2
Interior Light	Yes
Temperature Range	36°F to 43°F
Dimensions	
Interior Height	25.0" (64 cm)

Interior Width	19.38" (49 cm)
Interior Depth	17.38" (44 cm)
Compressor Step Height	3.75" (10 cm)
Compressor Step Width	19.38" (49 cm)
Compressor Step Depth	4.63" (12 cm)

