

SCRR232



83.75" x 27.5" x 31" (H x W x D)

23 cu.ft. commercial reach-in refrigerator in complete stainless steel

Highlights:

Commercially listed to NSF standards

Stainless steel interior and exterior cabinet for true durability in high traffic commercial settings

Optimized forced air cooling for excellent temperature stability and uniformity with rapid recovery after door openings and product loading

Product Features:

| | |
|---|---|
| Commercially approved | Commercial construction meeting UL commercial listing standards |
| Complete stainless steel construction | Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup |
| Forced air cooling | Top-mounted commercial fan ensures rapid temperature recovery |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |
| Self-closing door | Closes to save energy but will remain open when the door is opened at a 90° angle for easier loading |
| Open door alarm | Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will sound continuously if the door is open for more than 5 minutes |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| 6 inch casters | Ships with a set of casters (2 locking) for optional user installation |
| Microprocessor control panel | Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management |



SCRR232 Specifications:

| Overview | |
|----------------------------|---------------------|
| Height of Cabinet | 83.75" (213 cm) |
| Width | 27.5" (70 cm) |
| Depth | 31.0" (79 cm) |
| Depth with door at 90° | 56.5" (144 cm) |
| Capacity | 23.0 cu.ft. (651 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | UL |
| Canadian Electrical Safety | ULC |
| Sanitation | ETL-S |
| Amps | 7.5 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 282.0 lbs. (128 kg) |
| Shipping Weight | 292.0 lbs. (132 kg) |
| Estimated Time to Ship | 1 to 2 Days |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | No |
| Shelf Type | Wire |
| Shelf Qty | 4 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R290a |
| Refrigerant Amount | 2.5oz. |
| High Side PSI | 290.0 |
| Low Side PSI | 155.0 |
| Wheel Qty | 4 |
| Interior Light | Yes |
| Temperature Range | 33 to 41°F |
| Dimensions | |
| Interior Height | 51.5" (131 cm) |
| Interior Width | 23.5" (60 cm) |

Interior Depth 27.0"



