

# Speed Queen® Multi-Housing

## Quantum® Commercial Single Load Dryer

Rear Control



### BUILT FOR RELIABLE PERFORMANCE


- Secured coin vault meter case (coin only)
- Industry's largest door opening 2.06 sq. ft. (1914 cm<sup>2</sup>)
- Quiet, efficient blower system
- Door is reversible for installation flexibility
- End-of-cycle signal
- High efficiency exhaust blower with superior airflow 220 cfm (105 liters/sec)
- 100% serviceable from the front
- Space-saving narrow cabinet 26-7/8" (683 mm)
- Upfront lint filter easy to clean and secured
- Durable galvanized steel cylinder

### QUANTUM CONTROL

- Secured automated audits
- Easy-to-read digital display
- Cycle programming flexibility
- Multi-level vend pricing
- Individual cycle modifier keys
- Card and coin transactions
- Wash Alert™ with Service Alert capable



# QUANTUM® COMMERCIAL SINGLE LOAD DRYER SPECIFICATIONS

| MODELS and ACTIVATION   | SDENCRGS173TW02<br>SDGNCRGS113TW02  | SDENXRG173TW02<br>SDGNXRG113TW02  |
|---|-------------------------------------|---|
|   | {NOTE:<br>Coin Box Sold Separately} | <br>Coin "C" |
| <b>Appearance</b>   |                                     |   |
| Color   | White                               | White   |
| Top   | Porcelain                           | Porcelain   |
| Control Panel Selection   | Rear                                | Rear  |
| Meter Case  | High Capacity                       | High Capacity   |
| <b>Technical Info</b>   |                                     |   |
| Cylinder Volume cu. ft. (liters)  | 7.0 (198)                           | 7.0 (198)   |
| Cycle Temperature - High, Medium, Low, Delicate, No Heat                    |                                     |   |
| Motor (Capacitor Start and Thermal Protected) - 1/3 HP                      |                                     |   |
| Weight - lb (kg)  | Elec 135 (61)                       | 135 (61)  |
|   | Gas 140 (64)                        | 140 (64)  |
| Shipping Weight - lb (kg)   | Elec 145 (66)                       | 145 (66)  |
|   | Gas 150 (68)                        | 150 (68)  |
| Electrical Requirements   | 153 120/208/60/1-30 amp             | 120/240/60/1-30 amp*  |
|   | 173 120/240/60/1-30 amp*            |   |
|   | Gas 120/60/1-15 amp                 | 120/60/1-15 amp   |
| Overall Dimensions - WxDxH in (mm): 26 7/8 (683) x 28 (711) x 43 7/8 (1114) |                                     |   |
| Type Of Gas (Gas Models Only) ** Factory-Equipped Natural/Mixed Gas         |                                     |   |
| Air Outlet Diameter - in (mm)   | 4 (102)                             | 4 (102)   |
| Exhaust Airflow cfm (liters/sec)  | 220 (105)                           | 220 (105)   |
| Wireless Network Board Installed  | --                                  | --  |
| Heating Element   | 153 4750W, 208V                     | 5350W, 240V   |
|   | 173 5350W, 240V                     |   |
|   | Gas 25,000 Btu                      | 25,000 Btu  |
| <b>Performance/Features</b>   |                                     |   |
| Cycle Status Indicators   | Yes                                 | Yes   |
| Touch Pad Control with Sound Annunciator                                    |                                     |   |
| Agency Approval   | Elec cULus                          | cULus   |
|   | Gas cCSAus                          | cCSAus  |

\* Electric dryers come equipped for 120/240/60/1 operation. They can be field converted to operate on 120/208/60/1 with optional 61928 conversion kit.

\*\* Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO9001:2008.

