SPEED QUEEN MULTI-HOUSING

NOBODY COMPARES TO OUR GUTS

COMMERCIAL TOP LOAD WASHER

Built for Reliable Performance

Nobody compares with Speed Queen because you get more than quality products. You get peace of mind because you're dealing with a company that is committed to the multi-housing industry. You get the ongoing support of a national network of authorized Speed Queen Laundry Service Providers. And you get state-of-the-art electronic technology to maximize community laundry room profitability. What else would you expect from the world's leading supplier of commercial laundry equipment?

TOUCH PAD CONTROL allows for easy selection of hot, warm and cold water, and has 27 different cycle combinations to maximize fabric care.

CURVED, FOUR-VANE
AGITATOR delivers a 210°
agitation stroke, longest in the industry, for superb washing results.

DURABLE STAINLESS STEEL WASH TUB STANDARD won't corrode, chip, crack or pit in normal use.

TRIPLE-LIP SEAL for enhanced water seal of wash tub.

HEAVY-DUTY MOTOR

1/2 hp (0.37 kW), tub-mounted, two-speed motor for years of reliable performance, provides high 710 RPM spin speed.

RUGGED SUSPENSION with exclusive six "V" mounted springs provides superior handling of _____

unbalanced loads, reduces vibration and noise, and minimizes machine wear and tear.

START CAPACITOR reduces amperage draw for more efficient operation.

EASY-TO-READ DIGITAL

DISPLAY makes programming the machine a breeze and is easy to use, displaying vend price, cycle time and cycle status.



AUTOMATIC BALANCE SYSTEM (ABS) allows lateral motion of the washer module to improve performance and reduce noise.

INTEGRATED METER CASE

features superior meter caseto-top attachment for theft/ vandalism protection.

LARGE CAPACITY coin box standard.

COMMERCIAL GRADE

porcelain enamel top and lid for optimum durability.

PORCELAIN COATED STEEL

outer drain tub, resists mold and mildew.

EVERSMOOTH

TRANSMISSION is all metal and has only six moving parts for less maintenance and wear.

GALVANIZED STEEL base,

cabinet, front panel and meter case are precoated and corrosion-resistant for longlasting durability and backed by extended limited warranties.

POLYPROPYLENE PUMP

attaches directly to motor and can be conveniently accessed from front of the machine.



FEATURES

COMMERCIAL TOP LOAD WASHER



Quantum® Control Features: Digital display for vend price and cycle time countdown. Touch pad control with LEDs.

Three temperature selections for Hot, Warm or Cold water.

Three fabric selections for Normal, Permanent Press or

Delicate. Extra-large capacity with small load optional. Pushto-Start activation. Infrared programming.



Coin Slide Control Features: User selectable options for Hot, Warm or Cold wash temperatures. Two speeds with normal/gentle wash and slow/fast extract. Six total cycles with three "water saver" cycles and three regular cycles.

WATER MANAGER ADVANTAGES

OUANTUM® TOP LOAD DOE "J1" TESTING

WATER TEMP	НОТ	COLD	TOTAL WATER CONSUMPTION GAL (LITERS)	DOE CYCLE
Hot	5.4	19.2	24.6 (93.0)	14%
Warm	2.3	22.3	24.6 (93.0)	49%
Cold	0.0	24.6	24.6 (93.0)	37%

Modified Energy Factor (MEF) 1.69 (47.8) ft³/kWh/cycle (Liter/kWh/cycle) Water Factor (WF) 7.9 (1.06) liters/liter/cycle

COIN SLIDE TOP LOAD DOE "J1" TESTING

WATER TEMP	НОТ	COLD	TOTAL WATER CONSUMPTION GAL (LITERS)	DOE CYCLE
Hot	6.8	19.9	26.7 (101.0)	14%
Warm	2.8	23.9	26.7 (101.0)	49%
Cold	0.0	26.7	26.7 (101.0)	37%

Modified Energy Factor (MEF) 1.65 (46.7) ft³/kWh/cycle (Liter/kWh/cycle) Water Factor (WF) 8.4 (1.12) liters/liter/cycle

basket volume 3.26 (92.3)

QUANTUM® CYCLE DEFAULT AND PROGRAMMING

FEATURE	DEFAULT SETTING	OPTIONS
Wash Time	10 Minutes	0-10 Minutes
Deep Rinse	4 Minutes	0-10 Minutes
Spin	6 Minutes	0-10 Minutes
Vend Price	\$0.00	\$0.00 - \$655.00

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

