

The sculpted lines of Alta™ bring an exciting, new choice to typical range hood shapes. Sophisticated curves and hidden controls offer a beautiful alternative to traditional designs.

SIZE	BLACK	STAINLESS	WHITE GREASE FILTERS (replacement)		NON-DUCTED FILTERS	
30 in.	ALT130BL	ALT130SS	ALT130WW	HPFAMM30 (Type "C1" / "C2")	HPF30 (Type "Xc")	
36 in.	ALT136BL	ALT136SS	ALT136WW	HPFAMM36 (Type "D1" / "D2")	HPF36 (Type "Xd")	

HVI PERFORMANCE									
			Sones		CFM				
Duct Orientation	Size	Damper	Normal	High	Normal	High 0.25 in. w.g.	High 0.1 in. w.g.		
Vertical - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	140	130	220		
Horizontal - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	110	128	210		
Round - Vertical	7 in.	Sold Separately	1.5	5.0	150	110	240		

FEATURES					
Max. Blower Airflow	300 CFM				
Control type	2-speed Rocker				
Delay off	no				
Filter Clean Reminder	no				
Heat Sentry™	no				
ADA Capable	yes				
Lighting	2-level Halogen (included)				
Grease Filters	Micro Mesh (Qty. 2)				
Installation Hardware	EZ1 Bracket				
ENERGY STAR®	no				
Recirculation	Non-ducted filters sold separately				

## **AC INPUT**

120 V, 60 Hz - 1.4 AMPS

# OPTIONAL ACCESSORIES 7-in. Round Damper BP87Q

Make-up Air Dampers MD6TU, MD8TU and MD10TU


#### **MOUNTING HEIGHT**

18 in. to 24 in. from cooktop to bottom of hood


# LIMITED WARRANTY

1-year (See installation manual for full warranty text.)

### FOR INDOOR USE ONLY









SPECIFICATION SHEET



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.