## BRGAN<sup>®</sup> Elite

## **Under-Cabinet**

TENAYA

Tenaya is a slim, transitional design with gentle radius features which makes it perfect for todays contemporary kitchens. This beautiful design includes features that make it a pleasure to use and easy to maintain. The LED modules included with this hood are the latest in LED cooktop illumination technology specially designed to operate in the elevated temperatures of cooking - offering bright lighting and lasting up to 25 times as long as a standard bulb and greater reliability than typical replacement LED bulbs.

30 in. TEN230BL TEN230SX TEN230WW HPFAMM30 (Type "C1" / "C2") HPF30 (Type "X 33 in. TEN236BL TEN236SX TEN238WW HPFAMM36 (Type "D1" / "C2") HPF30 (Type "X 42 in TEN246SS TEN238WW HPFAMM36 (Type "D1" / "C2") HPF30 (Type "X 42 in TEN246SS HPFAMM42 (Type "E1" / "E2") HPF42 (Type "X HVI PERFORMANCE Duct Orientation Size Damper Normal Medium High Normal Medium 0.45 in.ws. 0 Hormal-Rectangular 31% in. x 10 in. Included 1.5 3.0 6.0 110 160 160 Horand-L Rectangular 31% in. x 10 in. Included 1.5 3.0 6.0 110 160 160 Horand-L Rectangular 31% in. x 10 in. Included 1.5 3.0 6.0 110 160 160 Horand-L Rectangular 375 CFM Max. Blower Airflow 375 CFM Control type 3-speed Capacitive Touch Delay off no Filter Clean Reminder yes Heat Sentry <sup>TM</sup> no ADA Capable yes Lighting 2-level LED (included) Grease Filters Micro Mesh (D), 2 Installation Non-ducted filters sold separately ADA Wring Kt HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTINK HEIGHT 13 in. to 24 in. from cooktop to bottom of hood Limited WaRANTY 1-year 	TERS	DUCTED FILT	NON	9			GREAS (repla		Έ	WHIT	SS	STAINLES		BLACK	SIZE
36 in.         TEN236BL         TEN236SS         TEN242SS         Image: Control of the contrecontrecontene control of the contrecontrol of the control of th	(c")	-30 (Type "Xc	HF	/ "C2")				/ HF	)WW	TEN230	SS	TEN2305	L	TEN230BL	30 in.
42 in.        TEN242SS        HPFAMM42 (Type "E1" / "E2")       HPF42 (Type "X)         HVI PERFORMANCE       Sones       CFM         Duct Orientation       Size       Damper       Normal       Medium'       High Normal       Medium'       0.25 in.wsp. 0         Vertical - Rectangular       3% in. x 10 in.       Included       1.5       3.0       6.0       110       160       160         Roand - Vertical       7 in.       Sold Separately       1.5       3.0       6.0       110       160       160         Roand - Vertical       7 in.       Sold Separately       1.5       3.0       5.5       120       180       140         FEATURES       Sapeed Capacitive Touch       Internet tens memoder       yes       Internet tens memoder </td <td>,</td> <td>: 51</td> <td></td> <td>,</td> <td></td> <td>36 in.</td>	,	: 51		,											36 in.
HY PERFORMANCE       Somes       CFM         Duct Orientation       Size       Damper       Normal       Medium*       High normal       Heigh normal <td></td> <td></td> <td></td> <td>,</td> <td></td>				,											
Duct Orientation         Size         Damper         Sones         CFM           Vertical - Rectangular         3% in. x 10 in.         Included         1.5         3.0         6.0         110         160         160           Vertical - Rectangular         3% in. x 10 in.         Included         1.5         3.0         6.0         110         160         160         160           Vertical - Rectangular         3% in. x 10 in.         Included         1.5         3.0         6.0         110         160         160         160           Sound - Vertical         7 in.         Sold Separately         1.5         3.0         5.5         120         180         140           FEATURES         Max. Blower Airflow         375 CFM         Sold Separately         1.5         3.0         5.5         120         180         140           Control type         3-speed Capacitive Touch         Elay off         no         Sold Separately         No         Sold Separ	,			,									-		
Duct Orientation         Size         Damper         Normal         Hedium         High D25 in. wg. 0           Vertical - Rectangular         3½ in. x 10 in.         Included         1.5         3.0         6.0         110         160         160           Horizontal - Rectangular         3½ in. x 10 in.         Included         1.5         3.0         6.0         110         160         160           Recurrent Vertical         7 in.         Sold Separately         1.5         3.0         5.5         120         180         140           FEATURES         Micro Mesh (Oty.         375 CFM         Stand - Vertical % Sold Separately         1.5         3.0         5.5         120         180         140           FEATURES         Micro Mesh (Oty.         375 CFM         Sold Separately         Nomediate for the sold separately         Nomediate for the sold separately         Nomediate for the sold separately           Macause Filter Clean Reminder         yes         Included)         State for the sold separately         Nomediate for the sold separately           McClinupt         Non-dected filters sold separately         Nomediate for the sold separately         Nomediate for the sold separately           McClinupt Coll         Non-dected filters sold separately         Nomediate for the sold separately		M	C				Sones								
vertical - Rectangular 3/k in x 10 in. Included 1.5 3.0 6.0 110 160 160 Round - Vertical 7 in. Sold Separately 1.5 3.0 5.5 120 180 140 FEATURES Max. Blower Airflow 375 CFM Control type 3-speed Capacitive Touch Delay off no Tilter Clean Reminder yes Heat Sentry <sup>TM</sup> no ADA Capabie yes Lighting 2-level LED (included) Grease Filters Micro Mesh (Oly. 2) nstallation Hardware EZ1 Bracket NeRGY STAR <sup>®</sup> no Recirculation Non-ducted filters sold separately ADA (Capabie Yes Lighting 2-level LED (included) Grease Filters Micro Mesh (Oly. 2) nstallation Hardware EZ1 Bracket NeRGY STAR <sup>®</sup> no Recirculation Non-ducted filters sold separately ADA Wring Kit HAWRK3 Make-up Air Dampers MD6TU, MDBTU and MD10TU MOUNTING HEIGHT 13 in. to 24 in. from cocktop to bottom of hood LIMIED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY	High	r				1				Damper	C	Size		Orientation	Duct 4
Horizontal - Rectangular 314 in x 10 in. Included 1.5 3.0 6.0 110 160 160 Round - Vertical 7 in. Sold Separately 1.5 3.0 5.5 120 180 140 FEATURES Max. Blower Airflow 375 CFM Control type 3-speed Capacitive Touch Delay off no Round Park Benninder yes Lighting 2-level LED (included) Grease Filters Micro Mesh (City. 2) Installation Hardware EZT Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS OPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wring Kt HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 13 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 1-year 1-	).1 in. w		ledium*	rmal	No	High	Medium*	rmal	Nor						
Round - Vertical 7 in. Sold Separately 1.5 3.0 6.5 120 180 140 FEATURES Max. Blower Airflow 375 CFM Control type 3-speed Capacitive Touch Delay off no Filter Clean Reminder yes Heat Sentry <sup>TM</sup> no ADA Capable yes Jighting 2-level LED (included) Grease Filters Micro Mesh (Oty. 2) Installation Hardware EZ1 Bracket EXERGY STAR <sup>®</sup> no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 In. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY	240										_				
FEATURES Max. Blower Airflow 375 CFM Control type 3-speed Capacitive Touch Delay off no Delay off no Period Capable yes Heat Sentry <sup>TM</sup> no ADA Capable yes Lighting 2-level LED (included) Grease Filters Micro Mesh (Ob. 2) Installation Hardware EZ1 Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-In. Round Damper BP870 ADA Wring Kit HAWRK3 MARe-up Ar Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in: to 24 in: from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 0 0 0 0 0 0 0 0 0	240										_		_	0	
Max. Blower Airflow 375 CFM Control type 3-speed Capacitive Touch Delay off no MAD Capable yes Leat Sentry <sup>TM</sup> no ADA Capable yes Lighting 2-level LED (included) Grease Filters Micro Mesh (Qty. 2) Installation Hardware EZI Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DOPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wiring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 19 in to 24 in. from cooktop to bottom of hood IMTITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 1-year 3-year (LED modules only) 5-y 100 150 20 25 30 350	260	140	180	20		5.5	3.0	1.5	1	I Separately	Sold	า.	7	Vertical	Round - \
Control type 3-speed Capacitive Touch Delay off no related Sentry <sup>TM</sup> no ADA Capable yes upthing 2-level LED (included) Grease Filters Micro Mesh (Oty. 2) nstallation Hardware EZ1 Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES T-in. Round Damper BP870 ADA Wining Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU WOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY I-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY														RES	EATUR
Delay off no indicating speed, or the second state of the second s												5 CFM	З	ower Airflow	Max. Blo
Filter Clean Reminder yes Heat Sentry <sup>TM</sup> no ADA Capable yes Lighting 2-level LED (included) Grease Filters Micro Mesh (Qty. 2) Installation Hardware E21 Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS OPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) COR INDOOR USE ONLY 0 0 0 0 0 0 0 0 0 0 0 0 0										Touch	citive	speed Capac	З		
Heat Sentry <sup>TM</sup> no ADA Capable yes ighting 2-level LED (included) Grease Filters Micro Mesh (Qty. 2) nstallation Hardware EZ1 Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DOPTIONAL ACCESSORIES 7-In. Round Damper BP87Q ADA Wiring Kit HAWRK3 Make-up Air Dampers MDBTU, MDBTU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 50 10 10 10 10 10 10 10 10 10 1															
ADA Capable yes Lighting 2-level LED (included) Grease Filters Micro Mesh (Oty. 2) nstallation Hardware EZ1 Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 0- 0- 0- 0- 0- 0- 0- 0- 0- 0-								_				5	r y		
Lighting 2-level LED (included) Grease Filters Micro Mesh (Qty. 2) nstallation Hardware EZ1 Bracket ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-in. Round Damper BP87Q ADA Wring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 0 0 0 0 0 0 0 0 0			(111) (111)										n	,	
Brease Filters       Micro Mesh (Oty. 2)         Installation Hardware       EZ1 Bracket         ENERGY STAR®       no         Recirculation       Non-ducted filters sold separately         AC INPUT       120 V, 60 Hz - 0.65 AMPS         DPTIONAL ACCESSORIES         7-in. Round Damper       BP870         ADA Wring Kit       HAWRK3         Make-up Air Dampers       MO6TU, MD8TU and MD10TU         MOUNTING HEIGHT       18 in. to 24 in. from cooktop to bottom of hood         LIMITED WARRANTY         I-year         3-year (LED modules only)         See installation manual for full warranty text.)         COR INDOOR USE ONLY         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0       0         0															
Installation Hardware EZ1 Bracket INERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 04 04 05 05 01 05 05 01 00 05 01 00 05 01 00 05 01 00 05 01 00 150 200 25 03 00 150 200 25 03 05 05 05 05 05 05 05 05 05 05	-	-						_		,			_		<u> </u>
ENERGY STAR® no Recirculation Non-ducted filters sold separately AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-in. Round Damper BP87Q ADA Wiring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 01 01 01 01 01 01 01 02 03 03 03 04 05 04 05 05 100 100 150 200 250 100 150 200 250 100 150 200 250 100 150 200 250 100 150 200 250 100 150 200 250 100 150 150 150 150 150 150 1								_		1	.ty. 2)		_		
Recirculation Non-ducted filters sold separately AC INPUT I20 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wiring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood IMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) COR INDOOR USE ONLY 0- 0- 0- 0- 0- 0- 0- 0- 0- 0-								_				1 Bracket			
AC INPUT 120 V, 60 Hz - 0.65 AMPS DPTIONAL ACCESSORIES 7-in. Round Damper BP870 ADA Wiring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) See installation manual for full warranty text.) FOR INDOOR USE ONLY 0-4 0-4 0-5 0-4 0-5 0-5 0-1 0-5 0-1 0-5 0-100 150 200 250 300 350														-	
120 V, 60 Hz - 0.65 AMPS OPTIONAL ACCESSORIES 7-in. Round Damper BP87Q ADA Wiring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0-4 0-5 0-5 0-5 0-5 0-5 0-5 0-5 0-5	and a state	- CONVERSION				-			ely	old separate	ers s	on-ducted filt	Ν		
OPTIONAL ACCESSORIES         7.in. Round Damper       BP870         ADA Wiring Kit       HAWRK3         Make-up Air Dampers       MD6TU, MD8TU and MD10TU         MOUNTING HEIGHT       18 in. to 24 in. from cooktop to bottom of hood         LIMITED WARRANTY         1-year         3-year (LED modules only)         (See installation manual for full warranty text.)         FOR INDOOR USE ONLY         0       0         0.3       0         0.4       0         0.4       0         0.5       100         0.4       0         0.5       100         0.4       0         0.5       100         0.4       0         0.5       100         0.4       0         0.5       100         0.5       100         0.6       100         0.7       100         0.8       100         0.9       100         0.1       100         0.2       100         0.3       100         0.4       100         0.5       100         0.5       100 <td></td> <td>0.0</td> <td>U Trans</td> <td>TO</td> <td></td> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>		0.0	U Trans	TO				4							
T-in. Round Damper BP87Q ADA Wiring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 0 0 50 100 150 200 250 300 350															
ADA Wiring Kit HAWRK3 Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0								4					_		
Make-up Air Dampers MD6TU, MD8TU and MD10TU MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 0 0 0 0 0 0 0 0 0							•	_							
MOUNTING HEIGHT 18 in. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0.6 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7								_						0	
18 in. to 24 in. from cooktop to bottom of hood LIMITED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 0 0 0 0 0 0 0 0 0			Ø						J	nd MD101U	IU ar	D610, MD8			
LIMITED WARRANTY 1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0- 0- 0- 0- 0- 0- 0- 0- 0- 0-			-					4		<u>.</u>					
1-year 3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0										100d	n of h	top to botton			
3-year (LED modules only) (See installation manual for full warranty text.) FOR INDOOR USE ONLY 0.4 0.3 0.4 0.3 0.4 0.3 0.4 0.3 0.4 0.3 0.4 0.3 0.4 0.3 0.5 0.4 0.3 0.5 0.4 0.3 0.5 0.4 0.3 0.5 0.4 0.5 0.4 0.3 0.4 0.5 0.4 0.4 0.5 0.4 0.4 0.5 0.4 0.4 0.5 0.4 0.4 0.5 0.4 0.5 0.4 0.5 0.4 0.5 0.4 0.5 0.4 0.5 0.7 1.n round High Speed, with 3X in. x 10 in. damper Horizontal High Speed, with 3X in. x 10 in. damper 0.1 0 0 50 100 150 200 250 300 350								4					Y	D WARRANTY	
(See installation manual for full warranty text.) FOR INDOOR USE ONLY						~						)			1-year 2 yoar (l
FOR INDOOR USE ONLY	2	,			2		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~			xt.)	tv tex	) or full warran	ual	stallation manual	See ins
0.6 0.7-in. round 0.7-in. round 0	$\geq$	× Sin		~						Ú.	Ĺ				
0.5 0.4 0.3 0.2 0.1 0 50 100 150 200 250 300 350 0.5 100 150 200 250 300 350			$\langle$	$\sim$									_		
0.3 0.4 0.3 0.2 0.1 0 0 50 100 150 200 250 300 350 0.2 0.1 0 50 100 150 200 250 300 350 0.2 0.3 0.2 0.5 0 100 150 200 250 300 350 150 100 150 200 250 300 350 150 100 150 100 150 150 100 150 15	13	R STOR					1.2					1			
0 50 100 150 200 250 300 350		0000 000000000000000000000000000000000				10 × 00	14		ed,						0.5
0 50 100 150 200 250 300 350						Co Co		_		7-in. round					0.5
0 50 100 150 200 250 300 350						Contraction of the second seco		ier -	ed,	7-in. round Vertical High Spee					0.5
0 50 100 150 200 250 300 350	lan-					10 × 10 × 10 × 10 × 10 × 10 × 10 × 10 ×			ed, n. dampe ipeed,	7-in. round - Vertical High Spee with 3¼ in. x 10 in - Horizontal High Sp					0.5
0 50 100 150 200 250 300 350	lons		2950			Contraction of the second seco			ed, n. dampe ipeed,	7-in. round - Vertical High Spee with 3¼ in. x 10 in - Horizontal High Sp					0.5 0.4 0.3 0.2
0 50 100 150 200 250 300 350		131 131 131 131 131 131 131 131 131 131	295				1		ed, n. dampe ipeed,	7-in. round - Vertical High Spee with 3¼ in. x 10 in - Horizontal High Sp					0.4
Airflow (cfm)			298						ed, n. dampe ipeed,	7-in. round - Vertical High Spee with 3¼ in. x 10 in - Horizontal High Sp					0.4 0.3 0.2 0.1
		131 131 131 131 131 131 131 131 131 131	298			10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -		ber	ed, n. dampe ipeed, n. dampe	7-in. round - Vertical High Spee with 3¼ in. x 10 in - Horizontal High Sp with 3¼ in. x 10 in				50 100	0.4 0.3 0.2 0.1 0

SPECIFICATION SHEET TEN2 SERIES

CERTIFIED

\* Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure