T23IR900SP

23.5-INCH BUILT-IN FRESH FOOD COLUMN



FREEDOM® COLLECTION, PANEL-READY



FEATURES & BENEFITS

- Freedom® Hinge enables true flush design
- The new Auto Door Opening provides the opening of the door with just a slight push or pull
- Delicate Produce Bins for expanded storage
- ThermaFresh System, Humidity and Temperature controlled drawers
- SoftClose® Drawers and Produce Bins for easy and controlled storage
- Sleek clean design for the perfect symmetry when paired with additional columns
- TFT control panel managing all your columns functions

TEMPERATURE RANGES		
Refrigerator	35°F (2°C) to 46°F (8°C)	
Temperature Controlled Drawer	32°F (0°C) to 46°F (8°C)	
Deli Drawer	Just above 32°F (0°C)	
Super Cool	35.5°F (2°C) for approximately 9 hours	
Energy Saving (Economy) Mode	45°F (7°C)	

Panel Ready	Yes
Reversible Door Swing	Yes
SoftClose® Drawers	Yes
Carbon Air Filter	Yes
Lighting	New Bar ALL LED Sidewall and Theater Lighting
Full Width Shelves	4
Adjustable Shelves	3
Shelf Material	Glass w/Aluminum Profile
Full Extension Drawers @ 115° Door Opening Angle	Yes
Full Extension Drawers @ 90° Door Opening Angle	Yes
Temperature and Humidity Controlled Drawer	1
General Use Drawer	1
Door Bins	2
Gallon Door Bins	1
Delicate Produce Bins	2 Small
Door Open Alarm	Yes
Open Door Assist	Yes
Special Modes	Sabbath, Economy, Vacation
CAPACITY	
Total Unit Gross Capacity (cu. ft.) – AHAM	13 cu. ft.
Refrigerator Gross Capacity (cu. ft.)	13 cu. ft.
PERFORMANCE	
Dedicated Evaporator & Compressor System	Yes
Freeflow® Cold Air System	Yes
SuperCool	Yes
TECHNICAL DETAILS	
Watts (W)	180 W
	1F A
Current (A)	15 A
Current (A) Volts (V)	120V-3 Prong
Volts (V)	
, ,	120V-3 Prong
Volts (V) Frequency (Hz)	120V-3 Prong 60 Hz
Volts (V) Frequency (Hz) Power Cord Length (in.)	120V-3 Prong 60 Hz 139
Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT	120V-3 Prong 60 Hz 139 120V-3 Prong
Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT Appliance Dimensions (H x W x D) (in.)	120V-3 Prong 60 Hz 139 120V-3 Prong
Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type	120V-3 Prong 60 Hz 139 120V-3 Prong 83 3/4"* x 23 1/4" x 2
Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT Appliance Dimensions (H x W x D) (in.) Required Cutout Size (H x W x D) (in.)	120V-3 Prong 60 Hz 139 120V-3 Prong 83 3/4"* x 23 1/4" x 2 84" x 23 1/2" x 25"
Volts (V) Frequency (Hz) Power Cord Length (in.) Plug Type DIMENSIONS & WEIGHT Appliance Dimensions (H x W x D) (in.) Required Cutout Size (H x W x D) (in.) Net / Gross Weight (lbs)	120V-3 Prong 60 Hz 139 120V-3 Prong 83 3/4"* x 23 1/4" x 25 84" x 23 1/2" x 25"

^{*}Height adjustable + / -1/2" (+ / -13 mm)

Page 1 of 3 09 / 17

23.5-INCH BUILT-IN FRESH FOOD COLUMN




FREEDOM® COLLECTION, PANEL-READY


WARRANTY	
Limited, Entire Appliance, Parts and Labor on Any Part of the Refrigerator that Fails Because of a Manufacturing Defect	2 Year
Limited Warranty for Sealed Refrigeration System**; Parts and Labor	3rd to 6th Year
Limited Warranty for Sealed Refrigeration System**; Parts Only	7th to 12th Year
Limited Warranty for Stainless Steel Rust-Through	Lifetime

 $^{{\}tt **Sealed}\ refrigeration\ system\ includes\ compressor,\ evaporator,\ condenser,\ dryer\ /\ strainer\ and\ connection\ tubing$

CUTOUT DIMENSIONS



TOP VIEW CLEARANCE



** Door handle must be added to this measurement

*Depends on the thickness of the unit door.

3/4" (19 mm) refers to the stainless steel door. (Special accessory).

Page 2 of 3 09 / 17


T23IR900SP

23.5-INCH BUILT-IN FRESH FOOD COLUMN





PANEL DIMENSIONS



ACCESSORIES (OPTIONAL)

STORAGE



SPRODBIN10 Small Produce Bin



LPRODBIN10 Large Produce Bin



24PRODRAIL 24-Inch Produce Railing



24HFGALBIN 24-Inch Half Gallon Bin

HANDLES

NOTE: Choose one handle for each column, choose 2 handles for each 2-door bottom freezer and choose 3 handles for each French Door bottom freezer.

PR36HNDL20

36-Inch Professional Series Handle PR30HNDL20

30-Inch Professional Series Handle

MS36HNDL20

36-Inch Masterpiece® Series Handle MS30HNDL20

30-Inch Masterpiece® Series Handle

PR36HNDL10

36-Inch Professional Series Classic Handle PR30HNDL10

30-Inch Professional Series Classic Handle

MS36HNDL10

36-Inch Masterpiece® Series Classic Handle MS30HNDL10

30-Inch Masterpiece® Series Classic Handle

HEATRKIT10 AND HEATRKIT20 FREEDOM® HEATER KIT

For installations where two appliances are installed side-by-side or instances where any appliances are installed less than 6" apart from another but not connected. The heater kit is also recommended for use with any installation in areas that are subject to humidity, or located next to an outside wall. HEATERKIT20 offers improved energy efficiency when compared to HEATRKIT10.

These warranties give you specific legal rights and you may have other rights that vary from state to state. Full warranty and limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada. Thermador is not responsible for products that are transported from the U.S. for use in Canada.

1 800 735 4328 | USA THERMADOR.COM | CANADA THERMADOR.CA | ©2017 BSH HOME APPLIANCES CORPORATION. ALL RIGHTS RESERVED.

Page 3 of 3 09 / 17