


400 Vario
Glass ceramic cooktop
 Width 15" (38 cm)



VC 422-610

- Special appliance for the professional kitchen. Individually combined for a consistent stainless steel design.
- Two cooking zones including combination. Output up to 4400 W.
- Great variability on a small surface.

Two cooking zones:

One Super-Quick cooking zone \varnothing 7 1/16" (1500 W), converts to \varnothing 9 1/16" (2400 W).

One Super-Quick cooking zone \varnothing 5 11/16" (1100 W), converts to 5 11/16" x 9 7/16" roasting zone (2000 W).

Electronic control in 12 output levels.

Combination indication.

Individual residual heat display.

Cooking zone marking.

Two control knobs with illuminous dials showing cooking position and setting.

Vacation lock.

Optional accessories:	VD 400-000 stainless steel cover.
	VV 400-000 Connecting strip for combination with other Vario cooktops (not when using a downdraft).
	VZ 400-700 Connecting strip with timer offers the automatic cooking time function for two appliances or cooking zones. Also, independent short-period alarm timer.

Planning notes:

Order cover and connecting strips separately.

Built-in control box is fitted in base cabinet at drawer level.

Panel thickness: 5/8" - 1".

Dimensions listed in cut-out drawing include spaces for connecting strips.

The VC422-610 does not come with an attached cable (hardwire required).

Clamping range: 1 3/16" - 2" cooktop fixings.

Rating:

Total rating: 4.4 kW
Total Amps: 19
220-240V / 60Hz

Front panel thickness 5/8" - 1".
 The sketch below must be observed if the panel is more than 1" thick (there must be a recess at the rear for proper control module installation).

