

# Viking Intelli-Wash™ 451 Series Dishwasher

## Vari-Pressure Intelli-Wash™ System – Exclusive

- Adjusts water volumes and water pressure
- Variable speed 1/2-horsepower commercial type-motor – **Exclusive**
- More power with less energy consumption – the Scrubbing Power™ leader in dishwashers
- Multi-level washing with two stainless steel wash arms
  - Largest and most powerful in history
  - Flexible-Fluid™ Coupling is block-proof and provides a direct water feed – **Exclusive**
- DishGuard™ Protector prevents blockage from lower rack load and protects dishes
- Sliding detergent/rinse agent dispenser

## Five-Stage Filtration and Waste Removal System – Exclusive

- Prevents redeposit of food particles to deliver spot-free dishes
- Removable coarse strainer
- Triple-Clean™ filtration
- Ultra-hard food waste disposer

## Sure-Temp™ Water Heating

- Automatically heats water to appropriate/selected temperature, assuring excellent washing results
- 1200-watt HydroFlo™ water heater

## Air-Flo™ Gentle Drying

- Gentle, effective, and safe fan-driven system delivers gentle air over, under, and around dishes

## Quiet Clean™ Performance Packages

- Engineered top to bottom for the quietest operation possible
  - Separate motor/pump assemblies for washing and draining
- Multi-stage sound-absorbing/heat-retaining insulation
- Blue LED “power on” light in kickplate indicates cycle is operating

## “Load-As-You-Like” Sturdi-Bilt™ Racks

- Accommodates 15 international place settings
- Fully useable and extendable nylon coated racks
- Two-piece silverware/cutlery basket with lids
- Lower Rack
  - Four rows of one-piece three-position fold-down tines
- Roller Bearing™ Upper Rack
- Three rows of multi-position Hold-Tight™ dividers – **Exclusive**
- 2 one-piece stemware cradle/cup shelves
- Side basket for large cutlery/utensils – **Exclusive**

## Cycles/Options

- Cycles – Pots/Pans, Normal Wash, Light/China, Fast Wash, Rinse/Hold
- Options – Hi-Temp Wash, Top Wash Only, Sanitized 155°F Rinse, Delay start up to 10 hours
- Clean Light
- Energy Star Qualified
- CEE Tier I Super Efficient
- NSF Certified



VDB451

Shown with new custom handle and endcap

## Models

- VDB451 – Professional door
- FDB451 – Accepts custom panel or optional Professional door panels

## Finish Options

- VDB451 available in Stainless Steel, Black, and White
- PDDP241 door panels available in 24 exclusive finishes and brass accent (BR) option

## Warranty Highlights

- Three-year full – complete dishwasher – Industry Exclusive
- Lifetime limited – tank and inner door
- Five-year limited – electronic controls, racks, motor/pump assemblies, and water distribution system
- Ninety-day limited – cosmetic parts such as glass, painted items, and decorative items



Professional Performance for the Home™

## Basic Specifications

Description	DISHWASHER
	VDB/FDB451
<b>Overall Width</b>	23 7/8" (60.6 cm)
<b>Overall Height from Floor</b>	33 7/8" (86.0 cm) min. to 35" (89.0 cm) max.
<b>Overall Depth from Rear with Door Panel Installed</b>	23 5/8" (60.0 cm) With door open – 49" (124.5 cm).
<b>Cutout Width</b>	24" (61.0 cm)
<b>Cutout Height</b>	34" (86.4 cm) min. to 35" (89.0 cm) min.
<b>Cutout Depth</b>	24" (61.0 cm)
<b>Electrical Requirements</b>	15.0 amps, 120 VAC/60 Hz; 3'9" (1.1 m) electrical cord with 90 degree 3-prong plug supplied with unit
<b>Water Heating Element Rating</b>	1200 watts
<b>Inlet Water Temperature</b>	120°F (49°C) recommended; Dishwasher will perform properly with cold water. Note: cycle times will be extended. 5' braided stainless steel hose with 3/8" OD compression fitting supplied with unit
<b>Drain Hose</b>	7' (2.1 m) long 1/2" (1.3 cm) ID "crimp-proof" flexible drain hose with clamp attached to dishwasher; connections provided for 5/8" (1.6 cm), 3/4" (1.9 cm), or 1" (2.5 cm), cut as required
<b>Drain Hose High Loop Required</b>	Height from floor – 20" (51.0 cm) min.
<b>Approximate Shipping Weight</b>	157 lbs. (71.2 kg)

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



Viking Range Corporation  
111 Front Street  
Greenwood, Mississippi 38930 USA  
(662) 455-1200  
For product information, call 1-888-VIKING1 (845-4641), or visit the Viking Web site at [vikingrange.com](http://vikingrange.com)

© 2012, Viking Range Corporation.

To receive the most current specification sheets, visit Dimension Express at [www.dexpress.com](http://www.dexpress.com) or call from your fax machine at (925)284-3558. Enter code #8051 for Viking Products. This will send you information on how to use the system and the corresponding model code numbers. Dimension Express customer support can be reached by email at: [support@dexpress.com](mailto:support@dexpress.com).