

Viking Undercounter/Freestanding Refrigerated Drawers

Features

- Electronic controls with digital temperature readout
- Temperature can be adjusted from 33 to 39 degrees F (6-3.9 degrees C); factory set at 34 degrees F (18.3 degrees C)
- Can be displayed in either Fahrenheit or Celsius
- 5.3 cubic feet of storage
- 200-lb. capacity full extension drawers
- LED lighting
- Energy Star qualified

Construction and Design

- Forced air cooling system
- Powerful 700 BTU compressor
- Stainless steel interior
- Stainless steel exterior cabinet
- Tru-Flush™ design allows refrigerator to fit flush into 24" deep installation cutout
- Undercounter or freestanding installation
- Door lock (outdoor model only)
- Super quiet 32-39 db sound rating
- Black kickplate (indoor model); stainless kickplate (outdoor model)
- Adjustable leveling legs

Models

- VRDI1240D – 24"W. Professional Refrigerated Drawer
- FRDI1240D – 24"W. Custom Panel Refrigerated Drawer
- VRDO1240D – 24"W. Outdoor Refrigerated Drawer

Finish and Design Options

- VRDI/VRDO models available in Stainless Steel (SS) only
- FRDI models accept custom panels

Optional Accessories

- Professional handle kit for custom front models – PHK23SS

Warranty Highlights

- Three-year full – covers complete unit/One-year full (Outdoor)
 - Six-year full – sealed system (Indoor only)
 - Lifetime limited – stainless steel exterior
 - 12-year limited – sealed system
 - 5-year limited (Outdoor)
 - Ninety-day limited – cosmetic parts such as glass, painted items, and decorative items
- * Warranty valid on Viking products shipped within the United States and Canada

Basic Specifications

Description	24"W. UNDERCOUNTER/FREESTANDING REFRIGERATED DRAWERS	
	VRDI/FRDI/VRDO1240	
Overall Width	23 7/8" (60.6 cm)	
Overall Height	34 1/4" (87.0 cm)	
Overall Depth from Rear	Without door panel: 23 5/16" (59.2 cm) To front of door panel: 24 1/16" (61.1 cm) To front of handle: 26 9/16" (67.5 cm)	
Cutout Width	24" (61.0 cm)	
Cutout Height	34 1/2"-35 1/2" (87.6-90.2 cm)	
Cutout Depth	24" (61.0 cm)	
Electrical Requirements	115V/60 Hz; 15 amp dedicated circuit; 5' power cord attached to product	
Maximum Amp Usage	3.0 amps	
Maximum Storage Capacity	5.3 cu. ft.	
Approximate Shipping Weight	215 lbs. (98 kg)	

Please do not prepare installation from brochure data only. See installation instructions for important clearance/installation information.



Viking Range Corporation
111 Front Street
Greenwood, Mississippi 38930 USA
(662) 455-1200

All models with standard equipment are design-certified for residential installation.

For product information, call 1-888-VIKING1 (845-4641), or visit the Viking Web site at vikingrange.com

© 2011, Viking Range Corporation.

To receive the most current specification sheets, visit Dimension Express at www.dexpress.com or call from your fax machine at (925)284-3558. Enter code #8051 for Viking Products. This will send you information on how to use the system and the corresponding model code numbers. Dimension Express customer support can be reached by email at: support@dexpress.com.