QUICK REFERENCE GUIDE > WB30SDEI1

Integrated Warming Drawer, 30"

Series 9 | Integrated

Panel Ready



Keep plates warm until ready to serve; rapid proof or slow cook. Panel-ready, you can match it with your cabinetry.

- Integrate your warming drawer into your surrounding cabinetry for seamless design
- Space to keep 16 standard-sized place settings evenly warm, with accessory rack for optimising space
- · Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	10 11/16"
Width	28 7/16"
Depth	22 3/16"

FEATURES & BENEFITS

Complementary design

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

Easy to clean

Cleaning and care of the Warming Drawer is simple. After each use, just wipe out the smooth glass interior with a damp cloth.

Easy to use

Soft-close with capacitive touch controls, our Warming Drawer comes with an accessory rack for optimising space.

Precise control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

Safe and sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

SPECIFICATIONS

Accessories

Professional round flush handle	Part 82139 (optional)
Square fine aluminium handle	Part 82105 (optional)
Square fine black handle kit	Part 82103 (optional)
Wire shelf	1

Capacity

Accessory rack maximum	42lk
Cappuccino cups	24
Espresso cups	54
Maximum allowable weight	55lbs
Place settings	16
Usable depth	16 1/16′
Usable height	9 1/16′
Usable width	27 1/2'

Cleaning

Easy clean smooth-glass base

Controls

Audio feedback

Automatic timers	30', 45', 1h, 2h, 4h, 6
Delayed start	
Electronic capacitive touch	
Pre-set heating functions	
Sabbath mode	
Soft close drawer	
Standby mode	

Functions

Cups •

QUICK REFERENCE GUIDE > WB30SDEI1 Date: 07.04.2022 > 2

Dehydrate	•
Number of functions	6
Plates	•
Rapid proof	•
Slow cook	•
Warm	•

Performance	
Heated glass base and fan	•
Low temperature cooking	•
Temperature levels	6
Temperature range	95°F-185°F

Power requirements	
Amperage	10A
Power outlet	3-prong grounding-type
Supply frequency	60Hz
Supply voltage	110V

Product dimensions		
Adjustable front door panel to	•	
Depth	22 3/16"	
Height	10 11/16"	
Width	28 7/16"	

Automatic turn off after 12	•
Full extension slides	•

W	arı	ar	ιtν

Safety

Parts and labor	2 years
SKU	82114

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Guide d'utilisation



Installation Guide



Data Sheet Integrated Warming Drawer

