HARMONIA





Four-speed IR "touch-free" control senses the finger location to activate the control without actually touching it. Lock-out mode to prevent false operation when cleaning.



LED lighting produces beautiful bright, clean light using minimal energy.



WC45 <i>i</i>	Q
---------------	---

Model Numbers:

Powered by the exclusive iQ Blower System[™] with GPS Technology (see page 62) for the quietest, most energy efficient and fastest smoke and odor removal available in a range hood; external blowers offered separately.

Glass and stainless steel intersect, joining together to form a beautiful union.

LED lighting has an extremely long lifespan; lamps may never need replacement.

Quick release, dishwasher-safe, mesh grease filters ensure a clean, fresh kitchen.

Heat Sentry[™] detects excessive heat and adjusts blower to high automatically.

Works with optional Universal Make-Up Air Dampers.

Hood Sizes Width Depth Finish St S F L Ν L L

T IIII JII	
Stocked	Brushed Stainless Steel with Glass
Special Order	Not Available
Features	
Lighting Type	LED 6-watts
Number of Lamps	2
Lighting Levels	1
Lighting Lamps Included	Yes
Control Type	4-speed Electronic "IR" Infrared
Control Features	Heat Sentry™, Delay Off, Filter Clean Reminder
Remote Control	Not Available
Filter Type	Mesh Grease Filter
Non-ducted Capability	Yes

35-7/16" (90cm)

17-11/16"

Hood Blower Included (WC45IQ)

Internal	iQ6	
Blower CFM	600	
Sones Low/High	0.3/7.5	
	· · · · · · · · ·	

Hood Blower Options (WC45E blowers sold separately)

External In-line	ILB3	ILB6	ILB9	ILB11
Max CFM	280	600	800	1100
Sone levels are typically	half of comparabl	e CFM int	ernal blov	wers.
External Exterior	EB6	EB9	EB12	EB15
External Exterior Max CFM	EB6 600	EB9 900	EB12 1200	EB15 1500

Accessories

Duct Direction


Backdraft Damper

10'-11' Flue Extension (Ducted) AEWC345IQSB 10'-11' Flue Extension (Non-ducted) AEWC345IQSBN Non-Duct Kit ANKWC345 Non-Duct Filter AFCWC345 Universal MUA Damper MD6TU, MD8TU, MD10TU

Installation Requirements

Amps @ 120V: Internal Blower Amps @ 120V: External Blower **Electrical Connection** Duct Size: Internal Blower Duct Size: External Blower

40 7.0 Max Plug In 8" 8" at hood (Transition to 10" typical, see pages 64-65) Vertical Included



Installation height above the cooking surface: 24"-30"

Telescopic flue for 8'-9' ceiling is standard. Optional flue extensions for 10'-11' ceiling

Reversible telescopic flue allows non-ducted recirculation. (see page 68)

For more details see the product specifications sheet found at www.BESTRangeHoods.com mority™