

Whirlpool® 30" Double Wall Oven WOD93ECOA

KEY FEATURES

- 30" Double Wall Oven
- True Convection System with Convection Conversion
- 5.0 cu. ft. oven capacity
- AccuBake® Temperature Management System
- Rapid Preheat
- Traditional Self-Clean System
- SteamClean Option
- FIT System
- New Whirlpool® Design
- •Hidden Bake

COLORS

White(W)

Black(B)

Stainless Steel(S)







Black w/Silver Handle(E) White w/Silver Handle(H)











Whirlpool® 30" Double Wall Oven WOD93ECOA


SPECIFICATIONS

MODEL # TRANSITIONED FROM MODEL # FEATURES (UPPER) Capacity (cu. ft.) True Convection System Self-Cleaning Rack Configuration	WOD93ECOA GBD309PV 5.0 Yes Yes with Steam Clean
FEATURES (UPPER) Capacity (cu. ft.) True Convection System Self-Cleaning	5.0 Yes
True Convection System Self-Cleaning	Yes
True Convection System Self-Cleaning	Yes
Self-Cleaning	Yes with Steam Clean
9	3 Racks with Integrated Handles
FEATURES (LOWER)	3
Capacity (cu. ft.)	5.0
Self-Cleaning	Yes with Steam Clean
Rack Configuration	2 Racks with Integrated Handles
GENERAL OVEN FEATURES	· ·
Bake Element (Watts) @ 240/208 V	2800/2427
Broil Element (Watts) @240/208 V	3600/3120
Broil Passes	8
Oven Cavity Size (in.)	18 in. H x 25 in. W x 19 in. D
AccuBake® Temperature Management System	Yes
Hidden Bake	Yes
Delay Bake	Yes
Sabbath Mode	Yes
Closed Door Broiling	Yes
Rapid Pre-heat	Yes
Rack Positions	6
Control Type	Membrane
Control Lockout	Yes
Oven Controls Display Type	VFD
Oven Controls Display Color	Blue / Red
Oven Light(s)	2 Incandescent
SPECIFICATIONS	
Power Supply Connection Location	3" Below Support Platform on Left or Right Hand side
Sales Demo Mode	Yes
Total Connected Load (kW) @ 240 volts	7.399
Total Connected Load (kW) @ 208 volts	5.607
Circuit (amps)	30
Approx. Shipping Weight (lbs.)	266
Handle Type	Metal
FIT System feet and trims supplied with oven	Yes
COLORS	W, B, S, E, H

W=White, B=Black, S=Stainless Steel, E=Black w/Silver Handle, H=White w/Silver Handle

DIMENSIONS

PRODUCT DIMENSIONS




30" (76.2 cm) models

- A. 51 1/16 " (130.6 cm) max. overall height
- B. 28½" (72.4 cm) max. recessed width
 C. 26½ " (124.0 cm) recessed

- D. 23 1/4" (59.1 cm) max. recessed depth
- E. 30" (76.2 cm) overall width

CABINET DIMENSIONS

Double Ovens Installed in Cabinet



30" (76.2 cm) models

- A. 30 " (76.2 cm) min. cabinet width

- width
 B. 1" (2.5 cm) top of cutout to
 bottom of upper cabinet door
 C. 14½, "(37.5 cm) bottom of
 cutout to floor
 D. 28½, " (72.4 cm) cutout width
 E. 1½, " (3.8 cm) min. bottom of
 cutout to top of cabinet door
 F. 50½, "(127.2 cm)"
 recommended cutout height
 G. 24" (60.7 cm) cutout depth

NOTE: The cutout height can be between $48^{29}\rm{/}_{32}$ " (124.1 cm) and $52^{19}\rm{/}_{64}$ " (132.6 cm) for double ovens.

CUTOUT DIMENSIONS	
Height	48 29/32 to 52 13/64
Width	28 1/2
Depth	24
Bottom of cutout to floor (in-wall)	14 3/4
PRODUCT DIMENSIONS	
Height	51 7/16
Width	30
Depth	26 3/8
Depth with door open 90 degrees	46 3/4

All dimensions are shown in inches.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.