









JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model



Solid Door Model

MODELS	DESCRIPTION		
HH24WS-4-1R/L	Indoor Shallow Depth Wine Reserve Solid Stainless Steel Door		
HH24WS-4-2R/L	Indoor Shallow Depth Wine Reserve Solid Panel Ready Door		
HH24WS-4-3R/L	Indoor Shallow Depth Wine Reserve Stainless Steel Glass Door		
HH24WS-4-4R/L	Indoor Shallow Depth Wine Reserve Panel Ready Glass Door		
HH24WO-4-1R/L	Outdoor Shallow Depth Wine Reserve Solid Stainless Steel Door		
HH24WO-4-2R/L	Outdoor Shallow Depth Wine Reserve Solid Panel Ready Door		
HH24WO-4-3R/L	Outdoor Shallow Depth Wine Reserve Stainless Steel Glass Door		
HH24WO-4-4R/L	Outdoor Shallow Depth Wine Reserve Panel Ready Glass Door		

KEY PRODUCT FEATURES AND BENEFITS

- Industry exclusive 18" shallow depth for ultimate design flexibility in tight spaces
- Industry's largest selection of ADA-height compliant models for accessible and aging in place designs
- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors

Quick Features:

- Perlick Anti-Condensation System[™] eliminates condensation from forming on the cabinet (outdoor models only)
- Wine shelves fully extend on vibration dampened, stainless steel ball-bearing glides; stainless steel wine shelves will not absorb odors over time
- Industry's best full 6 year warranty for owner ease of mind
- Commercial-grade all stainless steel interior and exterior provide superior durability and easy cleaning
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero global warming potential
- Storage for up to 20 bottles of wine



MODEL NUMBERS		HH24WS	HH24WO
MODEL DESCRIPTION		18" Indoor Wine Reserve	18" Outdoor Wine Reserve
ATTRIBUTES			
Perlick Anti-Condensation System		NO	YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm)	23-7/8" (606 mm)
	Depth - in. (mm)	18" (457 mm)	18" (457 mm)
	Height - in. (mm)	32" (813 mm)	32" (813 mm)
	Width - in. (mm)	24" (610 mm)	24" (610 mm)
OPENING DIMENSIONS	Depth - in. (mm)	18" (457 mm)	18" (457 mm)
	Height - in. (mm)	32-1/4" (819 mm)	32-1/4" (819 mm)
INTERNAL VOLUME Net. Cu. Ft. (L)		3.1 cu. ft.	3.1 cu. ft.
SHIPPING WEIGHT Lbs. (kg)		185 lbs (83.91 kg)	185 lbs (83.91 kg)
	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
ELECTRICAL SPECIFICATIONS	Running Load Amps	2.2 amps	2.2 amps
	Electrical Connection	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6′	6′
	Defrost Initiation	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle
	Thermostat	Digital	Digital
	Lighting Type	LED	LED
	Refrigerant	R600a (50g)	R600a (50g)
REFRIGERATION SPECIFICATIONS	Expansion Device	Capillary Tube	Capillary Tube
	Temperature Settings F°(C°)	45° (7.2°) - 65° (18.3°) Factory Set Point 36° (2.2°)	45° (7.2°) - 65° (18.3°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	350 BTU/hr	350 BTU/hr
	Pull Down Capacity	1000 BTU/hr	1000 BTU/hr
	Front Vented	Yes	Yes
PLUMBING		None Required	None Required

Installation Notes: To achieve 24" install depth, you must recess the outlet 7/8" into the wall directly behind the unit, or place electrical connection adjacent to the installation cavity.

ACCESSORIES

MODEL NOS.	DESCRIPTION	
(L)	Factory Installed Lock	
67992-L/R	Stacking Kit for HH24 models	
67115-24	Wood Faces for Wine Shelves (7/pk)	
67360	6"Toe Kick and Riser	

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit **perlick.com.**



CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HH24WS-4-1L	HH24WS4F-00-SLF0W	Left	No
HH24WS-4-1R	HH24WS4F-00-SRF0W	Right	No
HH24WS-4-2L	HH24WS4F-00-PL00W	Left	No
HH24WS-4-2R	HH24WS4F-00-PR00W	Right	No
HH24WS-4-3L	HH24WS4F-00-TLF0W	Left	No
HH24WS-4-3R	HH24WS4F-00-TRF0W	Right	No
HH24WS-4-4L	HH24WS4F-00-RL00W	Left	No
HH24WS-4-4R	HH24WS4F-00-RR00W	Right	No
HH24WS-4-1LL	HH24WS4F-00-SLFLW	Left	Yes
HH24WS-4-1RL	HH24WS4F-00-SRFLW	Right	Yes
HH24WS-4-2LL	HH24WS4F-00-PL0LW	Left	Yes
HH24WS-4-2RL	HH24WS4F-00-PR0LW	Right	Yes
HH24WS-4-3LL	HH24WS4F-00-TLFLW	Left	Yes
HH24WS-4-3RL	HH24WS4F-00-TRFLW	Right	Yes
HH24WS-4-4LL	HH24WS4F-00-RL0LW	Left	Yes
HH24WS-4-4RL	HH24WS4F-00-RR0LW	Right	Yes
HH24WO-4-1L	HH24WO4F-00-SLF0W	Left	No
HH24WO-4-1R	HH24WO4F-00-SRF0W	Right	No
HH24WO-4-2L	HH24WO4F-00-PL00W	Left	No
HH24WO-4-2R	HH24WO4F-00-PR00W	Right	No
HH24WO-4-3L	HH24WO4F-00-TLF0W	Left	No
HH24WO-4-3R	HH24WO4F-00-TRF0W	Right	No
HH24WO-4-4L	HH24WO4F-00-RL00W	Left	No
HH24WO-4-4R	HH24WO4F-00-RR00W	Right	No
HH24WO-4-1LL	HH24WO4F-00-SLFLW	Left	Yes
HH24WO-4-1RL	HH24WO4F-00-SRFLW	Right	Yes
HH24WO-4-2LL	HH24WO4F-00-PL0LW	Left	Yes
HH24WO-4-2RL	HH24WO4F-00-PR0LW	Right	Yes
HH24WO-4-3LL	HH24WO4F-00-TLFLW	Left	Yes
HH24WO-4-3RL	HH24WO4F-00-TRFLW	Right	Yes
HH24WO-4-4LL	HH24WO4F-00-RL0LW	Left	Yes
HH24WO-4-4RL	HH24WO4F-00-RR0LW	Right	Yes



