

BI-42UFDID/O



FEATURES

Discreet interior water dispense with advanced filtration

LED Lighting for brighter interior

Overlay design accepts cabinetry panels of all kinds

Maximum capacity in a 42" French door model

Dual refrigeration keeps food fresher longer

Air purification system fights spoilage, odors

Crispers and deli drawers in low-temp, high-humidity zones for optimum freshness

Microprocessor control assures peak performance

Two-column shelving for customized storage

Soft-close deli drawer for meats, cheeses and more

Freshness cards for maximum food preservation

Rigorously tested in our U.S. manufacturing facilities to ensure decades of use

Exceptional 24/7 support from Madison, WI-based Customer Care team

Over-and-under refrigerator/freezer storage

Magnetic door seal system locks in cold air

Automatic ice maker with "max ice" feature

Adjustable shelves for maximum convenience

ACCESSORIES

Stainless Steel Side Panel

White Side Panel

Air Purification Cartridge

Egg Container

Stainless steel kickplate

Grilles for 83" or 88" finished height (84" is standard)

Side panel mounting kit

Flush inset panels in stainless steel with tubular or pro handles

Full-length standard and extended framed handles

Framed front panels in white or stainless steel

Custom front panel mounting kit

Stainless steel pro handles

Stainless steel tubular handles

Accessories are available through an authorized Sub-Zero dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.



HANDLE ACCESSORIES



PRODUCT DETAILS

REFRIGERATOR

- 6 Adjustable glass shelves
- · 1 Stationary glass shelf
- 1 Deli drawer with dividers
- 2 Crisper drawers
- · 4 Adjustable door shelves
- · 2 Stationary door shelves
- · 2 Adjustable dairy compartments

FREEZER

- · Full-extension roll-out freezer drawer
- · Two-tier wire storage baskets
- · Automatic ice maker



PRODUCT SPECIFICATIONS

Model	BI-42UFDID/O
Dimensions	42"W x 84"H x 24"D
Door Clearance	22 1/4"
Drawer Clearance	23 5/8"
Weight	582 lb
Refrigerator Capacity	18.3 cu ft
Freezer Capacity	6.4 cu ft
Electrical Supply	115 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Plumbing Supply	1/4" OD copper, braided stainless steel or PEX tubing
Plumbing Pressure	35–120 psi
Receptacle	3-prong grounding-type

ELECTRICAL

7" (178) 6" (152) 751/2" (1918) FROM FLOOR RIGHT SIDE OF OPENING

PLUMBING




INTERIOR VIEW




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

DIMENSIONS



FLUSH INSET INSTALLATION



3 (76) typical depth. Shaded areas will be visible and should be finished to match cabinetry. NOTE: Shaded line represents profile of unit with *3/4* (19) panel.