



Buy it for looks. Buy it for life.®

# Specifications

## FAUCET DESCRIPTION

- Metal construction with various finishes identified by suffix
- Hydrolock® quick connect system
- Inlet shanks will accept 3/8" ball nose connections
- Pullout spray with 68" braided hose
- Lever style handle

## OPERATION

- Operates with less than 5 lbs. of force


## FLOW

- Aerator is limited to 2.2 gpm max. (8.3 L/min)

## CARTRIDGE


- 1225 cartridge design
- Nonmetallic, non-ferrous and stainless steel material

## STANDARDS

- Third party certified to CSA B-125.1, ASME A112.18.1 and all applicable requirements referenced therein including NSF61/9
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Water Drinking Act
- **ADA**  for lever handle

## WARRANTY


- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



**Camerist™**  
**Single Handle Pull-Down Bar Faucet**

**Models:** CA5955

**NOTE:** DESIGNED TO INSTALL  
THRU 2 HOLES 1-1/4" (25mm) MIN. DIA.  
and 4" (102mm) on center



## CRITICAL DIMENSIONS

(DO NOT SCALE)