

COMMERCIAL THROUGH RETAIL

COIN DROP

STACKED DRYERS AND STACKED WASHER- DRYERS



Product	Stacked Dryer	
	Tall	Short
Color	White	
Capacity - lb	18 each	
Cylinder Volume - cu.ft.	7.0 each	
Motor (Thermal Protected) - HP	0.33	
Type of Gas (Gas Models Only)	Factory Equipped Natural	
Available Cycles	High, Medium, Low, Delicate, No Heat	
Air Outlet Diameter - in	4	
Exhaust Airflow - cfm	220	
Electrical Requirements (v/Hz/Ph-Amp)	*Electric Gas	208-240/60/1-30 Amp 120/60/1-15 Amp
Heating Element	Electric Gas	5350W, 240V / 4750W, 208V 25,000 Btu
Net Weight - lb	270	
Shipping Weight - lb	280	
Shipping Dimensions Approx. - in	Width Depth Height	33 30 80
Agency Approvals	Electric Gas	cULus cCSAus
Model No.	SSENCAGS176TW01 SSGNCAGS116TW01	SSENCFGS176TW01 SSGNCFGS116TW01
Required Coin Kits (sold separately)	Quantity of 2 CK043	Quantity of 2 CK042

Note (not supplied): Each stacked dryer pocket requires its own power cord and the stacked washer-dryer requires two power cords, one for washer, one for dryer

For Commercial Use Only

Product	Stacked Washer-Dryer	
	Washer	Dryer
Color	White	
Capacity - lb	21	18
Cylinder Volume - cu.ft.	3.42	7.0
Spin Speed G-Force	440	–
Spin Speed RPM	1,200	–
Motor Size - HP	0.9	0.33
Type of Gas (Gas Models Only)	–	Factory Equipped Natural
Water Consumption Per Cycle - g (liter)**	13.68 (51.8)	–
IWF (Water Factor) - gal/ft3 (liters/liter/cycle)**	4.0 (0.53)	–
MEFJ2 (Modified Energy Factor) ft3/kWh/cycle (Liters/kWh/cycle)**	2.20 (62.3)	–
Available Cycles	Normal, Synthetic, Delicate	High, Medium, Low, Delicate, No Heat
Air Outlet Diameter - in	–	4
Exhaust Airflow - cfm	–	220
Electrical Requirements (v/Hz/Ph-Amp)	*Electric Gas	120/60/1-15 208-240/60/1-30 120/60/1-15
Heating Element	Electric Gas	– 5350W, 240V / 4750W, 208V 25,000 Btu
Net Weight - lb	385	
Shipping Weight - lb	417	
Shipping Dimensions Approx. - in	Width Depth Height	34 30 80
Agency Approvals	Electric Gas	cULus cCSAus
Model No.	STENCFSP176TW01	STGNCFS116TW01
Required Coin Kits (sold separately)	Quantity of 2 CK042	

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Stacked Dryer - Tall	16 7/8	78 1/6	28	15 4/9	23 1/2
Stacked Dryer - Short	26 7/8	76 1/2	28	15 4/9	23 1/2
Stacked Washer-Dryer - Short	26 7/8	76 1/2	27 3/4	14 1/2 ***	23 1/2

* Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.

** Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

*** For ADA compliance turn legs out from base 0.5 inches

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For additional accessories and warranty, please refer to the price list