

600 Series 30" Induction Range Top

F61RT304S1



Series	600
Series	ELECTRIC INDUCTION
Size	30"
Main Colour	SS
Logo	•
Stainless Steel Aestethics	Professional
	1 1010001011a1
Туре	INDUCTION
Cooking Surface	Ceramic Glass
Knobs	•
Induction Special Features	
Pot Detection System	•
Child lock function	•
Cooling fan system	•
Failure Codes indication	•
Induction Control Features	
Knob for power setting (illuminated)	•
Power levels	1 to 9
Digital display for power level indication	•
Melting Function 113°F / 45°C (inside the pot 108°F / 42°C) Warming Function 158°F / 70°C (inside the pot 149°F / 65°C)	•
Booster/Fast boil function for each zone	•
Heat up time automatic	•
Residual heat indication	•
Cooking Zones	4
Front Left	Inductor 9" (230mm)
Power (Min)	2300W
Power (Max)	3700W
Rear Left	Inductor 6" ½ (165mm)
Power (Min)	1400W
Power (Max)	2200W
Front Right	Inductor 7" 3/4 (200mm)
Power (Min)	1850W
Power (Max)	3000W
Rear Right	Inductor 7" 3/4 (200mm)
Power (Min)	1850W
Power (Max)	3000W
Dimensions	300077
Overall dim - width	29 3/4" (758mm)
	7" (179mm)
Overall dim - height Overall dim - depth	,
Cutout - width	29 3/4" (756mm)
	30" (762mm)
Cutout - height (min)	7" (179mm)
Cutout - depth (min-max)	24"- 25 1/2" (610-650mm)
Dower / Datings (200 /240)/ (0 11=)	
Power / Ratings (208/240 V, 60 Hz)	7 0144/ 204
KW/Amps rating at 120-240V, 60Hz	7,2kW - 30A
KW/Amps rating at 120-208V, 60Hz	6,45kW - 31A
Cable + Conduit	•
INSTRUCTIONS FOR USE	TN CD TD
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR