



Foglia features a gently arched front that softens the units profile and provides an angled panel for easy access to the controls. Available in 30" & 36" widths, Foglia includes a powerful 600 CFM blower, halogen lighting with 2 light intensities, stainless steel microhole filters and multi-function electronic controls with LCD display that deliver convenience and safety.

Designed for standard ducted installation, Foglia can also be installed as a recirculating system using the Recirculating Kit, available as an accessory.

MODELS

EFG630SM Foglia 30" Stainless EFG636SM Foglia 36" Stainless

DIMENSIONS

(30"W x 20"D x 10"H) (36"W x 20"D x 10"H)



Halogen Lamps



Multi-function electronic controls with LCD display



Stainless Steel Micro Hole Filters











Size (in) & Type 30" or 36" Wide Wall-Mount Chimney

Finish Stainless Steel

Controls Multi-function electronic controls with LCD display

Illumination 2, 40 Watt Halogen Lamps, 2 Light Intensities (bulbs included)

Installation Type Ducted or Recirculating Installation

Recirculating Kit Sold Separately

Blower Type 600 CFM, 4-Speed Internal

Blower Performance Speed 1, 210 CFM, 1.9 Sones

Speed 2, 300 CFM, 4.5 Sones Speed 3, 470 CFM, 7.9 Sones Speed 4, 600 CFM, 9.3 Sones

Dishwasher-Safe, Stainless Steel Micro Hole (2 w/ 30", 3 w/ 36") Filter Type

Telescopic Chimney Extension For heights 7'1" - 9'1" (ducted)

For heights 7'5" - 9'6" (recirculating)

Duct Transition 6" Round with Back Draft Damper (top)

Electrical 120V-60Hz

490 Watts at 4.1 Amps

Warranty 2 Year Parts & Labor, In-Home Service



Optional Recirculating Kit for 30" and 36" Units

CODE: KIT02766 MODEL: EXXRCK09



Optional Long Chimney Extension Kit Reaches 8'11" - 11'4" (ducted) Reaches 9'3" - 11'8" (recirculating)

CODE: KIT02784 MODEL: EXXCEK08

Replacement Grease Filter (1) CODE: GF04YB

Replacement Carbon Filter (1) CODE: KIT02667

Replacement Light Bulb (1) CODE: 2006BH

Consumable parts are sold in units of one (1). Order accordingly.

8 -1/16" 8 -1/8" 14 -1/8 24" * 28-15/16 min. 42-3/16 max. **28-7/8 min. 38-7/16 max. 10 -1/8'



Elica Heat Guard: A technology that protects the hood and cabinetry from excessive heat, by sensing extreme temperatures and automatically adjusting blower speeds accordingly.



Elica CRS: CFM Reduction System (CRS), is an exclusive feature to Elica hoods, which enables the installer to reduce the maximum blower CFM, to meet local code requirements.

