20AC 6032

	Cooling Capacity	BTU/Hr. @ ARI 80°F – 67° At 52% Relative Humidity	60,000
	Dimensions	Width (Inches)	28
		Depth (Inches)	39
		Height (Inches)	53
		Weight (Pounds)	470
		Shipping Weight	520
	Electrical	Power Supply (Volts)	208/230/60/3 Phase
	Characteristics	Power Consumption (Kilowatts)	5.9 Cooling
	• • • • • • • • • • • • • • • • • • •	Current Consumption (Amperes)	22 Cooling
		Fuse Size (Amperes)	40
		NEMA Plug Configuration	L15-30P
		Min-max Voltage	197-253 Volt
		Power Cord Gauge	10AWG (4 Core)
		Power Cord Length (Feet)	10
	Compressor	Compressor Type	Hermetic Scroll
	Characteristics	R 22 charge (Ounces)	77
		Operating Conditions: Min-max °F	55°-105°F, 50% RH
	Fan	Evaporator:	
	Characteristics	Fan Type 6 Speed	Reverse Curved
		Air Flow (CFM) High/Low	2000/1600
		Max. External Static Pressure	0.50
		(Inches Of Water Gauge)	
		Condenser:	
		Fan Type	Reverse Curved
		Air Flow (CFM)	3000
		Max. External Static Pressure	0.50
		(Inches Of Water Gauge)	
	Safety Devices	Compressor Overload Relay	Yes
	_	Fan Motor Protection	Yes
		Anti-freeze Thermostat	No
		Automatic Tank Shut-off (Adj. Level)	N/A
		Condensate Tank Capacity (Gallons)	Built In Pump
		High-pressure Switch	Yes
		Compressor Short-cycle Protection	Yes
		Fan Mode Switch	Yes
		Automatic Restart	Yes
		Thermostat	Digital
		Operating Cost (Approximate/Hr.)	\$0.62
	Features	Humidity Removed @ 60% RH (Gal/Hr.)	4.1
		Accommodates Condensate Pump	Built In Pump
		Sound Level (Db) High/Low	66/64
		Max Evaporator Ducting Length*(Ft.)	80
		Max Condenser Ducting Length*(Ft.)	80
		<u> </u>	- -
		*Subtract 10 Ft. For Every 90° Bend	

20AC 6032

Power Supply	208/230 volts	60 hertz	3 phase	22 amperes


Width 28 inches


Depth 39 inches


Height 53 inches


Weight (net/shipping) lbs 470/520

All models are backed by a 12-month warranty with 60 months for the compressor.









800.367.8675 · www.spot-coolers.com

Copyright © 2004 Spot Coolers, Inc. All rights reserved.

