

COMMERCIAL THROUGH RETAIL

PREP FOR CARD SINGLE DRYERS AND STACKED DRYERS



Product	Single Dryer	
	Rear Control	Front Control
Color	White	
Capacity - lb	18	
Cylinder Volume - cu.ft.	7	
Motor (Thermal Protected) - HP	0.33	
Type of Gas (Gas Models Only)	Factory Equipped Natural	
Available Cycles	High, Medium, Low, Delicate, No Heat	
Air Outlet Diameter - in	4	
Exhaust Airflow - cfm (liters/sec)	220	
Electrical Requirements (v/Hz/Ph-Amp)	*Electric Gas	208-240/60/1-30 120/60/1-15
Heating Element	Electric Gas	5350W, 240V / 4750W, 208V 25,000 Btu
Net Weight - lb	150	
Shipping Weight - lb	161	
Shipping Dimensions Approx. - in	Width Depth Height	30.5 29.5 45
Agency Approvals	Electric Gas	cULus cCSAus
Model No.	SDENYRGS176TW01 SDGNYRGS116TW01	SDENYAGS176TW01 SDGNYAGS116TW01

Product	Stacked Dryer	
	Tall	Short
Color	White	
Capacity - lb	18 each	
Cylinder Volume - cu.ft.	7.0 each	
Motor (Thermal Protected) - HP	0.33	
Type of Gas (Gas Models Only)	Factory Equipped Natural	
Available Cycles	High, Medium, Low, Delicate, No Heat	
Air Outlet Diameter - in	4	
Exhaust Airflow - cfm (liters/sec)	220	
Electrical Requirements (v/Hz/Ph-Amp)	*Electric Gas	208-240/60/1-30 Amp 120/60/1-15 Amp
Heating Element	Electric Gas	5350W, 240V / 4750W, 208V 25,000 Btu
Net Weight - lb	270	
Shipping Weight - lb	280	
Shipping Dimensions Approx. - in	Width Depth Height	33 30 80
Agency Approvals	Electric Gas	cULus cCSAus
Model No.	SSENAGS176TW01 SSGNYAGS116TW01	SSENYFGS176TW01 SSGNYFGS116TW01

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Single Dryer - Rear Control	26 7/8	43	28	15 4/9	23 1/2
Single Dryer - Front Control	26 7/8	44 1/3	28	15 4/9	23 1/2
Stacked Dryer - Tall	26 7/8	78 1/6	28	15 4/9	23 1/2
Stacked Dryer - Short	26 7/8	76 1/2	28	15 4/9	23 1/2

Note (not supplied): Each stacked dryer pocket requires its own power cord.
For Commercial Use Only

** Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V..

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For additional accessories and warranty, please refer to the price list.