COMMERCIAL
THROUGH RETAIL

PUSH-TO-START
TOP LOAD
WASHERS,SINGLE
DRYERS,AND STACKED
DRYERS

Product		Single Dryer Rear Control	
Color		White	
Capacity - lb (kg)		18	
Cylinder Volume - cu.ft. (liters)		7	
Motor (Thermal Protected) - HP		0.33	
Type of Gas (Gas Models Only)		Factory Equipped Natural/Mixed Gas	
Available Cycles		Normal, Perm Press, Delicate, No Heat	
Air Outlet Diameter - in		4	
Exhaust Airflow - cfm (liters/ sec)		220	
Electrical Requirements (v/Hz/ Ph-Amp)	*Electric Gas	208-240/60/1-30 120/60/1-15	
Heating Element	Electric Gas	5350W, 240V 25,000 Btu	
Net Weight - lb (kg)		150	
Shipping Weight - lb (kg)		161	
Shipping Dimensions Approx. - in	Width Depth Height	30.5 29.5 45	
Agency Approvals	Electric Gas	cULus cCSAus	
Model No.		SDEMNRGS173TW01	SDGMNRGS113TW01

Product		Stacked Dryer Tall	
Color		White	
Capacity - lb (kg)		18 each	
Cylinder Volume - cu.ft. (liters)		7.0 each	
Motor (Thermal Protected) - HP		0.33	
Type of Gas (Gas Models Only)		Factory Equipped Natural/Mixed Gas	
Available Cycles		Normal, Perm Press, Delicate, No Heat	
Air Outlet Diameter - in		4	
Exhaust Airflow - cfm (liters/ sec)		220	
Electrical Requirements (v/Hz/ Ph-Amp)	*Electric Gas	208-240/60/1-30 Amp 120/60/1-15 Amp	
Heating Element	Electric Gas	5350W, 240V / 4750W, 208V 25,000 Btu	
Net Weight - lb (kg)		262	
Shipping Weight - lb (kg)		272	
Shipping Dimensions Approx. - in	Width Depth Height	33 30 80	
Agency Approvals	Electric Gas	cULus cCSAus	
Model No.		SSEMNAGS173TW01	SSGMNAGS113TW01

Product		Top Load Washer
Color		White
Capacity - lb		16
Cylinder Volume - cu.ft.		319
Spin Speed RPM		710
Spin Speed G-Force		150
Motor Size - HP		05
Water Consumption Per Cycle - g (liter)**		28.07 (106)
IWF (Water Factor) - gal/ft3 (liters/liter/cycle)**		8.8 (1.18)
MEFJ2 (Modified Energy Factor) ft3/kWh/cycle (Liters/kWh/ cycle)**		1.35 (38.2)
Available Cycles		Normal, Delicate, Perm Press
Electrical Requirements (v/Hz/ Ph-Amp)		120/60/1-15
Net Weight - lb		206
Shipping Weight - lb		218
Shipping Dimensions Approx. - in	Width Depth Height	28 30 45
Agency Approvals	Electric Gas	cULus
Model No.		SWNMN2SP115TW01

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Single Dryer - Rear Control	26 7/8	43	28	15 4/9	23 1/2
Stacked Dryer - Tall	26 7/8	78 1/6	28	15 4/9	23 1/2
Top Load Washer	25 5/8	43	28	51	

Note (not supplied): Each stacked dryer pocket requires its own power cord.
For Commercial Use Only

* Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.

Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

** Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity

For additional accessories and warranty, please refer to the price list.