# MOEN

Buy it for looks. Buy it for life.®

# Specifications

FAUCET DESCRIPTION

- · Metal construction with various finishes identified by suffix
- Hydrolock<sup>®</sup> quick connect installation
- Pullout spray with 68" braided hose
- Flexible supply lines with 3/8" fittings connect directly to supply stops
- High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing
  360° rotating spout provides ability to install handle on either side
- OPERATION

#### Lever style handle

- Operates in stream or spray mode in the pullout or retracted position
- When filling a vessel outside the sink, the pause feature conveniently stops the water flow as the wand passes over the counter top
- Temperature controlled by 100° arc of handle travel

#### FLOW

• Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

#### CARTRIDGE


• 1255<sup>™</sup> Duralast<sup>™</sup> cartridge for Single-Handle Faucets

#### **STANDARDS**

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9
- Meets CalGreen and Georgia SB370 requirements
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Water Drinking Act
- The backflow protection system in the device consists of two
  independently operating check valves, a primary and a secondary which
  prevent backflow
- ADA ( for lever handle

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



# 90 DEGREE™ Single Handle High Arc Pull Out Kitchen Faucet

### Model: S7597 series

# **NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 HOLE, 1-1/2" (38mm) DIA.



