

SCFM162



Product Features:

UL-S listed to ANSI-NSF Standard 7 for commercial use Commercially approved Manual defrost operation Static cooling system Factory installed lock Keyed lock on the handle offers added security One piece interior liner Seamless interior ensures easier cleanup Adjustable thermostat Dial thermostat for easy temperature management Storage baskets Two removable plastic baskets offer convenient storage External "bumpers" are factory installed to protect the unit's front corners from dents Stainless steel front corner protectors White exterior Textured white finish fits well in any establishment 100% CFC free Environmentally friendly design without ozone-damaging chemicals

33" x 55.75" x 27.5" (H x W x D)

Commercially listed 16 cu.ft. manual defrost chest freezer

Highlights:

Commercially approved for use in foodservice establishments

Manual defrost operation and static cooling system

Added security with a factory installed lock





SCFM162 Specifications:

Overview	
Height of Cabinet	33.0" (84 cm)
Width	55.75" (142 cm)
Depth	27.5" (70 cm)
Capacity	16.0 cu.ft. (453 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	UL-S
Amps	5.0
Voltage/Frequency	115 V AC/60 Hz
Weight	170.0 lbs. (77 kg)
Shipping Weight	180.0 lbs. (82 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Refrigerator Features	
Door Swing	Lift-Up
Thermostat Type	Dial
Refrigerant Type	R134a
Temperature Range	-10 to 10°F
Dimensions	
Interior Height	29.13" (74 cm)
Interior Width	42.75" (109 cm)
Interior Depth	22.25" (57 cm)
Compressor Step Height	10.38" (26 cm)
Compressor Step Width	9.38" (24 cm)



