

BUILT FOR RELIABLE PERFORMANCE.

Speed Queen's commitment to multi-housing laundry is unmatched anywhere else in the industry. Built for performance and reliability, our laundry machines maximize your profitability and provide unparalleled convenience for your property.

Speed Queen®'s line of washers and dryers are ready to meet the demands of your laundry room. They are designed to work as a single or stacked laundry setup, provide maximum energy efficiency and long-lasting performance. Speed Queen front load laundry products have met every design standard to be 100% ADA compliant.

EQUIPPED WITH QUANTUM CONTROLS TO PROVIDE:

Total automated management of your laundry room. Its simple, powerful programming gives you the ability to:

- Easily manage your laundry operation with remote internet access.
- Establish multi-level vend prices, soil level cycles and dryer top-off times on your machines.
- Track coin or card transactions.
- WashAlert[™] with Service Alert capable.













Offering a variety of activation types allowing you to tailor your laundry room to fit your needs. Front control models all come with high capacity meter case.







Prep for Card ("Y")



Prep for Coin ("X")

FRONT LOAD WASHER





The Speed Queen front load washer gives building owners and property managers unparalleled ability to reduce water and energy costs through advanced programmability.

FEATURES

REVOLUTIONARY BALANCING TECHNOLOGY

Improved out-of-balance technology that uses a redesigned suspension and advanced sensing to manage and redistribute out-of-balanced loads, delivering uninterrupted cycles.

LOW WATER USAGE

Per cycle to reduce operating costs.

HIGH SPEED EXTRACT

1200 RPM final spin exerts 440 G-Force to maximize moisture removal from clothes.

LARGER DOOR OPENING

Extra wide 15.5" (394 cm) for easy loading and unloading of clothes.

STAINLESS STEEL WASH TUB

Comes with a lifetime warranty, and actually becomes smoother with each use, so it won't pill, snaq or fray clothes.

FOUR COMPARTMENT SUPPLY DISPENSER

Prewash, wash, fabric softener, bleach,



SINGLE LOAD DRYER



Speed Queen's front control dryer, defined by its simplicity and its performance, provides everything you need to get the job done – and nothing you don't. Speed Queen's single load dryers combine heavy-duty construction with reliable operation proven to stand the test of time. They're designed with less moving parts for one reason: so you'll face fewer maintenance problems and less wear and tear down the road. The perfect balance of heat, airflow and tumble action for optimal performance and efficiency.

FEATURES

SUPERIOR DRYING CONVENIENCE

With a $2.06 \, \text{sq.}$ ft. (1914 cm²) door opening, making it the widest in the industry, Speed Queen dryers offer the convenience of easy loading and unloading.

UPFRONT LINT FILTER

Easy to clean and secured.

REVERSIBLE DOOR (SOLID DOORS ONLY)

For installation flexibility.

EFFICIENT DRYER HEATING

 $25,000\ BTU$ (gas models) and $5,350\ Watts$ (electric models) provide fast drying and lower operating costs.



STACK DRYER

The Speed Queen stack dryer offers the same great features as the single load dryer. Two commercial dryers in the space of one, both operating independently, including independent controls for optimum usage. Available with see-through or solid door models. ADA Compliant (bottom dryer only).





STACK WASHER/DRYER



Speed Queen's stack washer/dryer bring an innovative stacked concept that takes up half the floor space that a conventional washer and dryer does when situated side by side. The freestanding softmount design can be installed on all floor types or levels. Both washer and dryer have the same hookups and connections as a standard washer and dryer. No additional plumbing or electrical change is needed. Same great features as the front control washer and dryer for superior washing and drying convenience. ADA Compliant (washer only).





QUANTUM® CONTROL COMMERCIAL WASHER & DRYER SPECIFICATIONS

COIN	Front Load Washer SFNNCASP113TW01 SFNNCASG113TW01 SFNNCAJP113TW01		gle Load Dryer SDENCAGS173TW01 SDGNCAGS113TW01	Electric 208: 240: Gas: Electric 208:	Stack Dryer SSENCAGS153TW01 SSENCAGS173TW01 SSGNCAGS113TW01 SSENCAGW153TW01	Stack V Electric 240: Gas:	Vasher/Dryer STENCASP173TW01 STGNCASP113TW01
MODELS and ACTIVATION	OF IN IVA OR A COT I VOA	FI	ODENINA 0045071404	240: Gas:	SSENCAGW173TW01 SSGNCAGW113TW01	EL	OTT 1/4 OD4 TO T 1/64
{NOTE: CARD Coin Box Sold Separately}	SFNNYASP113TW01 SFNNYAJP113TW01 SFNWYASP113TW01◊◊ SFNNYBSP113TW01 SFNNYASG113TW01	Electric 208: 240: Gas: Electric 208: 240: Gas:	SDENYAGS173TW01 SDGNYAGS113TW01	Electric 208: 240: Gas: Electric 208: 240: Gas: Electric 240: Gas: Electric 240: Gas: Electric 240: Gas: Electric 240: Gas:	SSENYAGS153TW01 SSENYAGS113TW01 SSENYAGS113TW01◊◊ SSEWYAGS153TW01◊◊ SSEWYAGS113TW01◊◊ SSENYAGW173TW01 SSENYAGW113TW01 SSGNYAGW113TW01◊◊ SSEWYAGW173TW01◊◊ SSGWYAGW113TW01◊◊	Electric 240: Gas: Electric 240: Gas:	STENYASP173TW01 STGNYASP113TW01 STEWYASP173TW010 STGWYASP113TW0100
	SFNNXASP113TW01	-		Electric 240: Gas:	SSENXAGW173TW01 SSGNXAGS113TW01	Electric 240: Gas:	STENXASP173TW01 STGNXASP113TW01 STGNXASG113TW01
Stainless Basket/Cylinder Volume - cu.ft. (liters)	3.42 (96.8)	7.0 (198)		7.0 (198) ea po	ocket	3.42 (96.8) 7.0 (19	3)
Width-in (mm)	267/8 (683)	267/8 (683)		26 7/8 (683)		267/8 (683)	
Depth - in (mm)	27 3/4 (704)	28 (711)		28 (711)		27 3/4 (704)	
Height* - in (mm)	443/8 (1126)	443/8 (1126)		78 3/16 (1986)		78 3/16 (1986)	
Weight-lb(kg)	270 (122.5)	Electric: Gas:	150 (68) 155 (70)	Electric: Gas:	265 (120) 275 (125)	Electric:	390 (177)
Shipping Weight - lb (kg)	290 (131.5)	Electric: Gas:	160 (73) 165 (75)	Electric: Gas:	280 (127) 290 (132)	Electric:	425 (193)
Cycle Time - minutes (default)	27	45		45		27/45	
Motor HP (Capacitor Start and Thermal Protected)	0.9 HP 671 W	1/3 HP, 5.5 am	nps	1/3 HP, 5.5 am	ips	0.9 HP 671 W 1/3 HP, 5.5 amps	
Water Consumption - gal (Liter)	11.7 (44.3)	N/A		N/A		11.7 (44.3)	
Water Factor - gal/ft³ (Liters/Liter/cycle)	3.8 (0.52)	N/A		N/A		3.8 (0.52)	
Modified Energy Factor - ft³/kWh/cycle (Liters/kWh/cycle)	2.98 (84.48)	N/A		N/A		2.98 (84.48)	
Average Hot Water Usage - gal (Liter)	0.4 (1.5)	N/A		N/A		0.4 (1.5)	
Water Pressure PSI (Bar)	20-120 (1.4-8.3)	N/A		N/A		20-120 (1.4-8.3)	
Spin Speed - RPM	500,800,1200	N/A		N/A		500,800,1200	
Cycle/Temperature	Hot Normal Warm Perm Press Cold Delicate	High Medium Low Delicate No Heat	160° 155° 145° 115°	High Medium Low Delicate No Heat	160 ° 155 ° 145 ° 115 °	WASHER Hot/Normal Warm/Perm Press Cold/Delicate	DRYER High/160 ° Medium/155° Low/145° Delicate/115° No Heat
Electrical Specifications and Circuit Requirements	120/60/1-15 amp	Electric: Gas:	208/60/1-30 amp 240/60/1-30 amp* 120/60/1-15 amp	Electric: 2 ea Gas: 2 ea	208/60/1-30 amp 240/60/1-30 amp* 120/60/1-15 amp	WASHER DRYER Electric: Gas:	120/60/1-15 amp 208/60/1-30 amp 240/60/1-30 amp* 120-60/1-15 amp**
Btu per Hour (kcal)	N/A	25,000 (6300))	25,000 (6300)	25,000 (6300)	
Heating Element	N/A	4750W, 208V 5350W, 240V		4750W, 208V 5350W, 240V		4750W, 208V 5350W, 240V	
Type of Gas (Gas models only)	N/A		pped natural/mixed ble to LP gas**		oped natural/mixed	Factory-equipped gas convertible to	
Utility Connections - in (mm)	N/A	Gas: 3/8 NPT	(9.5)	Gas: 3/8 NPT	(9.5)	Gas: 3/8" NPT (9.5)	
Air Outlet Diameter - in (mm)	N/A	4 (102)		4(102)		4(102)	
Exhaust Airflow - cfm (liters/sec)†	N/A	220 (105)		220 (105)		220 (105)	
Maximum Exhaust Static Back Pressure	N/A	0.6" W.C.		0.6" W.C.		0.6" W.C.	
Agency Approval		Electric:	cULus	Electric:	cULus	Electric:	cULus
Activation Activation	cCSAus Coin/Card Op	Gas: Coin/Card Or	cCSAus	Gas: Coin/Card Or	cCSAus	Gas: Coin/Card Op	cCSAus
Top and Lid Finish	Porcelain	Porcelain		N/A		N/A	
Colors	White	White		White		White	
DoorType	Window	Solid		Solid, Windo	AI.	Window	
31		N/A			IV.	N/A	
Supply Injection	Yes			N/A			
Drain	Pump or Gravity	N/A		N/A		Pump or Gravity	
Wireless Network Board Installed◊◊	Yes	Yes		Yes		Yes	

NOTE: Each stack dryer pocket requires its own separate power cord. | Stack washer/dryer requires two power cords - One for washer, one for dryer.

- Electric dryers come equipped for 240/60/1 operation. They can be field converted to operate on 208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.
- ** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the U.S.A.

