

# ARC COLLECTION

## SURFACE<sup>WALL</sup>

For minimalism with depth and contrast, dark glass always lends drama to the contemporary stainless steel kitchen. No angles here. Just clean, straight lines bisected by a slim plane of transparent gray glass. Dual halogens and a remote control put this wall-mount range hood's reflective play of power and light right in your hands.



	SIZE	NET WIDTH	COLOR
<b>ASU-M90ASX</b>	36"	35 3/8"	Stainless Steel/ Transparent Gray Glass
<b>ASU-E42ASX</b>	42"	42"	Stainless Steel/ Transparent Gray Glass



RF Remote Control

# ARC COLLECTION

## SURFACE WALL

### MODEL

ASU-M90ASX	36"
ASU-E42ASX	42"

### FEATURES

Controls	Memory Touch Glass
Speed Levels	3
Auto Delay-Off	Yes
CleanAir Function	Yes
Remote Control	Yes, RF
Lighting	Halogen, 20W x 2
Tri-Level Lighting	Yes
Filters	Decorative Mesh x 1
Recirculating	Yes
Duct Cover Extension	Yes

### \*PERFORMANCE

Internal Blower - CBI-290A	290 CFM, 3.2 Sones Max.
Internal Blower - CBI-600A	600 CFM, 6 Sones Max.
In-Line Blower - PBN-1000A	1000 CFM, Sones NA
External Blower - CBE-1000	1000 CFM, Sones NA

### AC INPUT

120V - 60Hz

### \*\*AC POWER

Hood Only Max. 40W, 0.33 Amps

### MOUNTING HEIGHTS

Height from the cooking surface Min. 24" - Max. 36"

### HOOD HEIGHTS

#### Standard

Minimum Ducted	27"
Minimum Recirculating	32"
Maximum	47"

#### Extension Kit - Z1C-00SU

Minimum Ducted	43"
Minimum Recirculating	48"
Maximum	79"

### DUCT SPECIFICATIONS

Vertical - Internal	6"
Vertical - In-Line/External	10" to 8"***
Horizontal	NA

### OPTIONAL ACCESSORIES

Recirculating Kit	ZRC-00SU
Duct Cover Extension Kit (12' ceiling)	Z1C-00SU

\*Requires purchase of Zephyr blower, sold separately. \*\*AC power listed above is for hood with lights only. See blower specs on our website for more AC power details. \*\*\*10" round duct connects to external and in-line blower. Must transition from 10" to 8" before duct passes through ceiling. A 10" to 8" adapter is included with the external and in-line blowers.

