## **OWC 3612**

<b>Cooling Capacity</b>	BTU/Hr. @ 80°F Air Temperature 85°F Entering Water Temperature	36,100
	<u> </u>	
<b>Dimensions</b>	Width (Inches)	29
	Depth (Inches)	15
	Height (Inches)	47
	Weight (Pounds)	240
	Shipping Weight	270
Electrical	Power Supply (Volts)	208/230/60/1 Phase
Characteristics	Power Consumption (Kilowatts)	3.0 Cooling
Characteristics	Current Consumption (Amperes)	13.0 Cooling
	Fuse Size (Amperes)	20
	NEMA Plug Configuration	6-20P
	Min-max Voltage	195-250 Volt
	Power Cord Gauge	14AWG (3 Core)
	Power Cord Length (Feet)	10
Compressor	Compressor Type	Hermetic Scroll
Characteristics	R 22 charge (Ounces)	36
Characteristics	Operating Conditions: Min-max °F	55°-105°F, 50% RH
	Operating Conditions. Will max 1	55 1051, 50% KH
Fan	Evaporator:	
<b>Characteristics</b>	Fan Type 6 Speed	Centrifugal
	Air Flow (CFM) High/Low	1310/1048
	Max. External Static Pressure	0.25
	(Inches Of Water Gauge)	
Condenser	Automatic Water Regulating Valve	Yes
Water Flow	Inlet Water Temp. 85°F-95°F Exit	9.00 GPM
TTACCI I IOW	Inlet Water Temp. 75°F–95°F Exit	5.20 GPM
	Inlet Water Temp. 65°F–95°F Exit	3.50 GPM
	Inlet Water Temp. 55°F–95°F Exit	2.60 GPM
	• • • • • • • • • • • • • • • • • • • •	
Miscellaneous	Thermostat	Yes
<b>Features</b>	Built-in Condensate Pump with 20Ft. Lift	Yes
	Check Valve with Safety Switch	Yes
	High-Pressure Switch	Yes
	Water Connections (supply and return)	5/8 Inch MF
	Condensate Connection	3/8 Inch MF
	Hose Kits Available 10'-25'-40'	Yes
	Optional Heat Pump Unit Available	No
	Optional Tower Application Unit Available	Yes
	Sound Level (Db) High/Low	64/62
	•	
	* available in 208/230/3 phase	

\* available in 208/230/3 phase

## **OWC 3612**

Power Supply 208/230 volts 60 hertz 1 phase 13 amperes


Width 29 inches


Depth 15 inches


Height 47 inches

Weight (net/shipping) lbs 240/270 lbs

All models are backed by a 12-month warranty with 60 months for the compressor.









800.367.8675 · www.spot-coolers.com