

Combination Built-in Oven


PRODUCT MODEL NUMBER

WOC97ES0E

ELECTRICAL CONNECTION

To properly install your oven, you must determine the type of electrical connection you will be using and follow the instructions provided for it here.

 Oven must be connected to the proper electrical voltage, amperage, and frequency as specified on the model/serial/ rating plate. See the following illustration.



A. Model/serial/rating plate

- Models rated from 7.3 to 9.6 kW at 240 volts (5.4 to 7.4 kW at 208 volts) require a separate 40-amp circuit. Models rated at 4.8 kW and below at 240 volts (3.6 kW and below at 208 volts) require a separate 30-amp circuit.
- A circuit breaker is recommended.
- If the house has aluminum wiring, follow the procedure below:
 - 1. Connect a section of solid copper wire to the ends of the flexible conduit leads.
 - Connect the aluminum wiring to the added section of copper wire using special connectors and/or tools designed and UL listed for joining copper to aluminum.

Follow the electrical connector manufacturer's recommended procedure. Aluminum/copper connection must conform with local codes and industry-accepted wiring practices.


For power requirements for models, refer to the following table.

Voltage	Amperage (L1)*	Amperage (L2)*	Rating (W)	
120/240	32	30	8.0 kW	
120/208	30	28	6.6 kW	

*Amperage values noted above are for information purposes only: The units are rated in watts.

PRODUCT DIMENSIONS


30" (68.6 cm and 76.2 cm) Ovens



- A. 42%16" (108.0 cm) overall height
- B. 28⁷/16" (72.2 cm) recessed width
- C. 41" (104.1 cm) recessed height
- D. 231/4" (59.1 cm) max. recessed depth
- E. 30" (76.2 cm) overall width
- F. 48" (121.9 cm) flexible conduit length measured from the conduit clamp located at the rear of the oven. Do not remove the conduit clamp.

CABINET DIMENSIONS

30" (68.6 cm and 76.2 cm) Ovens



- A. 30" (76.2 cm) min. cabinet width
- B. 1" (2.5 cm) top of cutout to bottom of upper cabinet door
- C. 19¹/4" (48.9 cm) bottom of cutout to floor is recommended.
- 4"–19¹/4" (10.2–48.9 cm) bottom of cutout to floor is acceptable. D. 28¹/2" (72.4 cm) cutout width
- E. 11/2" (3.8 cm) min. bottom of cutout to top of cabinet door
- F. 415/16" (105 cm)* recommended cutout height
- G. 24" (60.7 cm) cutout depth

***NOTE:** The cutout height can be between 41" and 41¹/₂" (104.1 cm and 105.6 cm) for microwave/oven combination.